

TOWCHLOR

Active Ingredient: Sodium dichloro-S-triazinetrione dihydrate	99.0%
Inert Ingredient	1.0%
Available Chlorine	56.0%

DANGER

KEEP OUT OF REACH OF CHILDREN

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly Corrosive. Causes skin and eye damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

PRACTICAL TREATMENT (FIRST AID): If **swallowed** feed bread soaked in milk followed by olive oil or cooking oil. Call a physician immediately. If **on skin**, brush off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention. If **in eyes**, flush with cold water for at least 15 minutes. Get medical attention.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES Permit. For guidance contact the regional office of EPA.

PHYSICAL AND CHEMICAL HAZARDS

STRONG OXIDIZING AGENT: Mix only with water. Use clean, dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases and possible generation of fire and explosion. In case of contamination or decomposition, do not reseal container. If possible isolate container in open air or well ventilated area. Flood with large volumes of water if necessary.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

Suhm Towchlor industrial water biocide is recommended for use in industrial cooling water.

Industrial Cooling Tower Water

For badly fouled systems add 1½ or 3 lbs. of Towchlor industrial water biocide daily for each 10,000 gallons of system water. This provides 10 ppm and 20 ppm available chlorine respectively. Repeat each day until the system is free of visible fungus and algal slime. This condition is usually indicated when a free available chlorine residual of at least 1 ppm is found four hours after the treatment. When a system is under control add 5 or 10 oz. of Towchlor industrial water biocide daily per 10,000 gallons of system water to provide 2 or 4 ppm free available chlorine respectively. These amounts may be raised or lowered as required and indicated by water conditions and by test for chlorine residual. Reliable test kits for testing free available chlorine are available and should be used. Towchlor industrial water biocide should be added directly from the container to a place in the system where it will be evenly mixed with the water.

STORAGE AND DISPOSAL

Keep product dry in tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat or open flame. In case of decomposition isolate container, if possible, and flood with large amounts of water to dissolve all material before discarding. Place in trash collection or dispose in approved landfill area or bury in a safe place.

Manufactured by:
Suhm Laboratories, Inc.
6901 Industrial Loop
Greendale, WI 53129-0099

EPA REG. NO. 10600-7

EPA EST. NO. 10600

NET CONTENTS: 50 LBS.