

SL-88 ALGACIDE FOR INDUSTRIAL RE-CIRCULATING WATER COOLING SYSTEMS

WATER SYSTEMS CLEAN AND FREE OF BACTERIAL AND ALGAL SLIMES



Growths Are
of water in
ning hours.
it.

ACTIVE INGREDIENT:	
Calcium Hypochlorite.....	5.00%
INERT INGREDIENTS.....	<u>95.00%</u>
	100.00%

CAUTION:

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. If swallowed feed milk or egg white, call physician. May cause sever skin and eye irritation. In case of contact with skin and eyes, flush with plenty of water.

Do not mix with other chemicals, especially acids, as this may result in the release of hazardous gases.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label.

Do not reuse container. Destroy when empty.

When used as directed, SL-88 will aid in controlling and/or preventing the development of unsanitary slime conditions which are unsightly, produce foul odors and which are often the cause of equipment breakdown.

Do not be alarmed with the sudden appearance of a considerable amount of organic debris in the system during the first week of operation. This is normal and is a good indication that SL-88 has effectively penetrated and dislodged dead organic material which tenaciously adheres to metal and wooden surfaces as living matter. This debris should be removed from the systems to avoid clogging of the screens and pipes.

SL-88 is compatible with virtually all corrosion inhibition additives, and products normally used in cooling water systems but should not be used in conjunction with acidic materials.

For best results, clean heavily contaminated systems before treatment with this product. Apply SL-88 at a point in the system where uniform mixing will take place. Add this product on distribution decks, tower basin or sump.

NET CONTENTS: _____ Gallons

E.P.A. Reg. No. 10663-18
E.P.A. Est. 10663 - Ga. - 1



1481 ROCK MOUNTAIN BOULEVARD • STONE MOUNTAIN, GEORGIA 30083

SUPER AL-JAX

Non-Foaming Swimming Pool Algaecide

DESCRIPTION

The presence of algae in outdoor swimming pools is objectionable because of the color, cloudiness, odor, and increased chlorine demand of the water. The use of this algaecide will help to maintain the water in a clean condition.

This algaecide is compatible with the usual water treatment chemicals. By controlling algae growth with this algaecide, the chlorine demand of the pool may be significantly reduced.

CAUTION

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. Avoid contamination of food. Rinse empty container thoroughly with water and discard container. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies. This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Apply this product only as specified on this label.

ACTIVE INGREDIENT:

Poly[oxyethylene(dimethyliminio)ethylene(dimethyliminio)-ethylene dichloride].....10.0%

INERT INGREDIENT.....90.0%

100.0%

Weight Per Gallon.....8.49 lb.

Weight of Active Ingredients Per Gallon.....0.85 lb.

CAUTION

KEEP OUT OF REACH OF CHILDREN

See left panel for additional cautions.

E.P.A. Reg. No. 10663-21

E.P.A. Est. 10663-GA-1

NET CONTENTS _____ GALLONS

Manufactured By

This algaecide is used in swimming pools. It is a non-foaming product containing heavy grade chlorine. To use this product, add to pools having just been cleaned. For pools having just been cleaned, use a dose of 75 to 115 gallons of water per gallon of water being cleaned.

For treatment of a pool, initially 41 to 75 ft. To maintain pools, frequent additions of water should be made. Treatment.

Uniform distribution of water in the pool is important. This algaecide is a chemical normally used and is effective at a pH of 7.5. This algaecide, when treated with chlorine, will reduce the amount of chlorine normally required. Apply this product with liquid chlorine product.