

LESTER CHEMICAL COMPANY

1039 West Wal: Springfield, Missouri

HY-TEST

SODIUM HYPOCHLORITE

USDA Reg. No. 9146-1

PLANTS FOOD PROCESS PLANTS
WATER TREATMENT MOLD CONTROL

ACTIVE INGREDIENT - Sodium Hypochlorite - 10.2%
OTHER INGREDIENTS - 89.8%

CAUTION

KEEP OUT OF REACH OF CHILDREN.
See panel for additional precautionary labeling.

NET CONTENTS: 1 U.S. GALLON

HY-TEST

Springfield, Missouri, U.S.A.

POISON

IRRITATING TO EYES,
SKIN AND LUNGS

 ANTIDOTE 
EXTERNAL

WASH WITH WATER
INTERNAL

DRINK MUCILAGE, RAW
EGG WHITE, MILK OR
RICE GRUEL, FOLLOW
WITH EMETIC (TABLE-
SPOONFUL OF MUSTARD
IN GLASS OF WATER.

CALL A PHYSICIAN

Do not mix HY-TEST with acid
detergents.

Use dilute solutions only as directed
on label.

ACCEPTED

NOV 1 1968

UNDER THE
FUNCTION
FOR EGGS
AND UNDER 9146-1

10671-4

POULTRY and EGG PROCESSING

After the cleaning of eviscerating, pasteurizing, inspection and other processing equipment, sanitize before use with a 200 ppm solution of available chlorine by spray or recirculation methods for a period of not less than two minutes.

MOLD CONTROL WITH HY-TEST

Scrub and wash moldy surfaces until clean. Spray all surfaces with 5000 ppm of available chlorine solution. Relative humidity and ventilation determine partly the growth of mold and the Spraying Interval.

INSTITUTIONAL SANITIZATION WITH HY-TEST

HY-TEST liquid sodium hypochlorite is excellent for treating food service equipment. Use a 200 ppm solution, allowing all surfaces and parts to be exposed to the germicide for a period of two minutes. Equally effective when used to bleach out wood top tables, cutting blocks, steam table boards using 800 ppm of available chlorine. Always use on equipment after a thorough clean up job. Equipment must be rinsed, after sanitizing, with potable water.

WATER TREATMENT WITH HY-TEST

MUNICIPAL and WATER FARM SUPPLIES

Common practice is to chlorinate water until there is a residual of 0.2 to 0.5 ppm available chlorine. Suitable testing apparatus must be used to determine the amount of sodium hypochlorite required. Test the water 10-20 minutes after adding HY-TEST.

SWIMMING POOL CHLORINATION WITH HY-TEST

RECIRCULATING POOL WATER

HY-TEST should be added to maintain a residual of 0.6 to 1.0 ppm of available chlorine. This product should be used in conjunction with a chlorine test kit and added to the pool in sufficient quantity to insure that the residual chlorine in the pool water is maintained at a minimum concentration of 0.6 parts per million at all times. The pH of the pool water should be maintained between 7.2 and 7.6.