

Chemquest 202

NOT REVIEWED
In Accordance with E. Notice 82-2,
Based on Draft Labeling Dated

ACTIVE INGREDIENT

Polyoxyethylene/dimethylamine/dithyrene
(dimethylamine/dithyrene dichloride)

3%

INERT INGREDIENTS

97%

This product contains 2.7 lb. of active ingredient per gallon and weighs 9.1 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk or egg white. Do not induce vomiting if these are recommended. Drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.



DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with the labeling.

Chemquest 202 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. For its use, systems must be cleaned to remove all growth from both the coils and other deposits. An initial dosage of 1.00 to 1.25 lb. of Chemquest 202 per 1000 gallons of water is applied. A maintenance rate of 16 to 30 parts per million of Chemquest 202 is used to treat 1000 gal. of water in the system every 24 hours. Repeat if the algae or bacteria are not controlled.

Subsequent dosages of 0.47 to 0.75 lb. of Chemquest 202 per 1000 gallons of water (4 to 6 parts per million) may be employed every 2 to 5 days, as needed. The frequency of treatment depends on the relative amount of growth and the quantity of the maintenance application. A minimum of 1000 gal. of water cooling towers.

Chemquest 202 is used to control bacteria in industrial cooling systems that maintain effective rust-inhibiting components. Prior to its use, systems should be cleaned to remove all rust and scale. An initial dosage of 1.1 to 11.9 lb. of Chemquest 202 per 1000 gallons of water is recommended. Repeat if a large amount of rust is present. Subsequent dosages of 1.5 to 11.9 lb. of Chemquest 202 per 1000 gallons of water should be employed every 1 to 5 days, as needed. The frequency of application depends upon the relative amount of rust and the quantity of the previous application. A minimum of 1000 gal. of water cooling towers.

STORAGE AND DISPOSAL

Store in a cool, dry place. Do not store in direct sunlight. Do not store in a damp or wet place. Do not store in a place where children or pets can reach. Do not store in a place where it can be used for other purposes. Do not store in a place where it can be used for other purposes. Do not store in a place where it can be used for other purposes.

EMPTY CONTAINER: Wash thoroughly with water. Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes.

CONTAINER DISPOSAL: Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes.

Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes. Do not reuse for other purposes.

Manufactured by
Ely-Krom

11402 Sursum Road
Compton, CA 90221

EPA Reg. No. 1-1093-21

EPA EST. NO.

NET CONTENTS