# ACCEPTED

### DEC 0 9 1986

i the lederal heacticide, line, and Re lanticide L. Chemquest 203-A Hog. No. 10693-25

#### **ACTIVE INGREDIENTS:**

Disodium cyanodithioimidocarbonate ..... 7.35% INERT INGREDIENTS ...... 82.50% TOTAL ...... 100.00%

This product contains 1.62 lb. of active ingredients per gallon and weighs 9.25 lb. per gallon.

### KEEP OUT OF REACH OF CHILDREN

## WARNING

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed, Avoid contamination of food.

STATEMENT OF PRACTICAL TREATMENT: In case of contact, immediately flush eyes or skin with plenty of yoter for at least 15 minutes. For eyes call a physician. Remove and wash contaminated clothing before rauce. If swallowed, call & physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of Miroat with finger. Do not Induce vomiting or give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this active ingredient into lakes, streams, police, estuaries, oceans, or public waters unless this product is specifically identified and acdressed in को NPDES permit. Do not discharge affluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

### **DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Chemquest 203 is used to control algae and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 3.3 to 6.6 fluid ounces of Chemquest 203 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 1.1 to 6.6 fluid ounces of Chemouest 203 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

#### STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous W representative at your EPA Regional Office for guidance.

### CONTAINER DISPOSAL:

- METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.
- [] PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning, if burned, staylout of smoke.

Manufactured by: Flo-Kem, Inc. 19402 Susana Rd.

Compton, CA 90221 EPA REG. NO. <u>10693-25</u> EPA EST. NO. \_\_\_\_

NET CONTENTS \_\_\_\_\_