•

ATTACHMENT IS APPLICABLE

Enclosures

SIGNATURE OF APPROVING OFFICIAL

DATE

EPA Form 8570-6 (Rev. 5-76)

PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

: NTS

CHEMQUEST 600

Jail02 1987

Dated:

Strate Act un pesticide **ACTIVE INGREDIENTS:** · LPA Reg. No. Methylene bis(thiocyanate) 10693-26 10%

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workmen handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

FIRST AID: In case of skin contact, wash promptly and thoroughly with soap and water and finally with glycerin. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for 15 to 30 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person. ENVIRONMENTAL HAZARDS: This posticide is toxic to fish. Do not apply in marine

and/or estuarine oil fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specificalty identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

	Manufactured by: FLO-KEM, INC.	
	19402 SUSANA RD.	
•	COMPTON, CA 90221	
EPA REG. NO	EPA Est. No.	

NET CONTENTS ___

DIRECTIONS FO

It is a violation of Federal law to use this product in

COOLING TOWERS: _ CHEMOUEST 600 wood against soft or surface rot and internal or dry rot. If sion containing 0.5 to 0.7% by weight __CHEMOUES' wood surfaces. The amount applied should provide 0.6 t

per 1000 ft.2 of wood surface. Soft or surface rot can a CHEMQUEST 600 __ to the reck cold wall. The dosage should provide 1.25 lb, of __.CH 1000 gal, of water, and the bleedoff should be stopped to

ment should be repeated every four months.

COOLING WATER: CHEMOTIEST 600 and fungi in industrial recirculating cooling water system should be cleaned thoroughly to remove old algal growth System should then be drained, flushed, refilled with we 3.7 fl. oz of CHEMQUEST 600 quent additions of 0.2 to 1.2 ft. oz. per 1000 gal. should

amount of bleedoff and severity of microbiological fouli DRILLING FLUIDS: To inhibit bacterial and fungal degraing of wells, CHEMQUEST 600 centrations of 0.05 to 0.25% based on the total wet we

PETROLEUM SECONDARY RECOVERY: CHEMQ control sulfate-reducing bacteria, slime-forming bacter micellar floods, water-disposal systems, and other oil-fl 13.0 fl. oz. of CHEMQUEST 600 should be made continuously or intermittently by me knockouts, before or after injection pumps and injection

When system is noticeably fouled, add 3.9 to 13.0 fl. oz. per 1000 gal. of water continuously until desired degree 13.0 fl. oz. CHEMQUEST 600 13.0 fl. oz. ___ needed to maintain control, Intermittent or Slug Met maintain control, add 3.9 to 13.0 fl. oz. ___CHEMQUE of water for 4 to 8 hr. per day and 1 to 4 times per we CRUDE AND REFINED OILS: CHEMQUEST 600 vative for the control of bacteria and fungi that cause th during storage. It should be added to the oil as it is bei

the storage tank at the rate of 0.6 to 6.0 fl. oz. ___C

1000 gal, of oil, Addition should be made batchwise with

tion side of the transfer pump.

STORAGE & D

Do not contaminate water, food, or feed by storage or STORAGE: Do not expose to extreme temperatures. D should be opened in well-ventilated areas. Leaking or d drums for disposal. Spills should be absorbed in sawdus PESTICIDE DISPOSAL: Pesticide wastes are acute pesticide, spray mixture, or rinsate is a violation of Feder by use according to label instructions, contact your Stat or the Hazardous Waste representative at your EPA Re CONTAINER DISPOSAL: Triple rinse (or equivalent). puncture and dispose of in a sanitary landfill, by inc

airthorities, by burning. If burned, stay out of smoke.