

A Baker Hughes company

MAGNACIDE® 434

Active Ingredient:

1-(Alkyl* amino)-3-aminopropane

hydroxyacetate 48.0 wt. %

'as in coconut oil fatty acids

Inert Ingredients 52.0 wt. %

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS ...

Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. May be harmful or fatal if swallowed or absorbed through skin. Avoid contamination of food. Do not breathe vapor or spray mist. Wash thoroughly after handling.


STATEMENT OF PRACTICAL TREATMENT

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available drink large quantities of water. Avoid alcohol. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavago. Measures against circulatory shock, respiratory depression and convulsion may be needed

ENVIRONMENTAL HAZARDS

This posticide is toxic to fish. Do not apply to marine and/or estuarine oil fields. Do not dischargo elfluent containing this product into lakes, streams, ponds, estuaries, occans or other wastes unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notlifed in writing prior to discharge. Do not discharge effluent containing this product to sawer systems without previously notifying the local sewage treatment plant authority. For guidance contact your Stato Water Board or Regional Office of the EPA.



FOR TREATMENT OF OIL FIELD INJECTION WATER SYSTEMS DIRECTIONS FOR USE

It is a violation of federal law to use the product in a manner inconsistent with its label. For use with closed delivery systems only.

MAGNACIDE 434 is offective in control of suffate reducing bacteria and slime forming bacteria in oilfield waters. High concentrations of salts or specific ions may impair the effectiveness of MAGNACIDE 434.

OILFIELD INJECTION SYSTEMS

MAGNACIDE 434 should be added to the water handling system at a point of uniform mixing such as the area of addition of make up water to the holding tank.

CONTINUOUS INJECTION: Add MAGNACIDE 434 at 1 part per 10,000 parts water (4 gal per 1000 bbl water) when system is noticeably fouled. When microbial control is evident, add 1 part MAGNACIDE 434 per 20,000 parts water (2 gal per 1000 bbl water) to maintain control.

BATCH TREATMENT: When microbial control is evident, add MAGNACIDE 434 at 1 part per 10,000 parts water (4 gal per 1000 bbl water) over a period of 6 hours several timos per week.

STORAGE AND DISPOSAL

- 1. PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal.
- STORAGE: This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not use, pour, spill or store near heat or open flame.
- PESTICIDE DISPOSAL: Pesificide wastes are acutely hazardous. Improper disposal of excess
 posticido, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed
 of by use according to labol instructions, contact your State Pesticide or Environmental Control
 Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
 CONTAINER DISPOSAL
 - METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and depose of in a sanitary landfill, or by other procedures approved by state and local authorities.
 - PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanilary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL: Consull lederal, state or local disposal authorities for approved alternative procedure.

Notice of Warranty


Our recommendations for use of this product are based upon lests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.

MANUFACTURED BY: BAKER PETROLITE CORPORATION 3900 Essex Lane, Houston, TX 77027

EPA Reg. No. 10707-5

EPA Est. 10707-CA-001

NET WEIGHT



PG 1097

5

11/14/97

ω

 $\langle y \rangle$