MAGNACIDE 656 MICROBIOCIDE will control algae and bacterial stimes found in recirculating cooling tower waters and oil field water floods. MAGNACIDE 656 MICROBIOCIDE helps clean and loosen stime debris from cooling and flooding system surfaces. When used in alug doses, no other microbiocide is required.

Precautionary Statements Hazards to Humans and Domestic Animals DANGER .:

Keep Out of Reach of Children. Corrosive. Causes severe eyr and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fistal if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge treated effluent into lakes, streams, ponds or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the Environmental Protection Agency.

STORAGE AND DISPOSAL

- 1. PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal.
- 2. STORAGE: This product is corrosive to mild steel. Do not store or transport in unlined metal containers.
- 3. PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label Instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

4. CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. GENERAL: Consult federal, state or local disposal authorities for approved alternative procedure.

DEST AVAILABLE COM

BAKER PERFORMANO

101/01/-27

MAGNACIDE® 656 MICROBIOCIDE

Twin-Chain Quaternary Ammonlum Compound Concentrate Water Treatment Microbiocide for Building and Industrial Cooling Towers and Oil Field Water Flood or Salt Water Disposal Systems

Active Ingredient Didecyl dimethyl ammonium chloride 50% Inert Ingredients

KEEP OUT OF REACH OF CHILDREN DANGER

Statement of Practical Treatment

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution; or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

> SEE LEFT PANEL FOR **ADDITIONAL PRECAUTIONARY STATEMENTS EPA REG. NO 10707-24** EPA EST. NO. 10707-OK-002 10707-TX-001 10707-CA-012

ACCEPTED

DIRECTIONS FOR USE GENERAL CLASSIFICATION

is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

To control algae and becterial silmes, use MAGNACIDE 656 MICROBIOCIDE as directed. For best results, slug feed. The trequency of addition of microblockie needed depends on many factors. To optimize your use of MAGNACIDE 656 MICROBIOCIDE, follow this procedure:

Recirculating Cooling Towers

1. Initially use 6 fluid ounces per 1000 gallons of water to be treated (20 ppm active quaternary). Should the above dosage not give satisfactory results, use 9 fluid ounces per 1000 gallons of weter. Repeal. the initial dose every seven days or increase the troquency if needed.

2. When the above treatment level is successful, use 2 to 3 fluid ounces per 1000 gallons of water to maximize efficiency. Repeat weekly as needed.

Should stir a develop again, go back to initial dosage. Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of these dosages; slug leed every seven days.

Daute the appropriate amount of MAGNACIDE 656 MICRO-BIOCIDE in 1 or 2 gallons of water, then add to the lower. Note, this product weighs 7.73 lbs. per gallon (at 20°C). Should tower be heavily fouled, a precleaning is required.

Oil Field Water Flood or Salt Water Disposal Systems: (Do not apply in Marine or Estuarine Oil Fields).

1. For the control of stime forming and suitale reducing bacterial in cilfield water flood or salt water discosal systems, add 5-10 ppm (active) MAGNACIDE 658 MICROBIOCIDE (11/2-3 gallons per 3000 barrels of water) continuously. Levels for effective control will very depending on conditions at the site.

2. For intermittent use, dose at a rate of 5-20 ppm (active) MAGNACIDE 656 MICROBIOCIDE (11/2-6 gallons per 3000 barrels of water) for 4-8 hours per day, one to four times a week as needed to maintain control

Add MAGNACIDE 656 MICROBIOCIDE directly from the drum with the proper type of metering equipment. This product weighs 7.73 lbs/gallon (at 20°C)

Net Welght Net Volume

400 lbs. 55 gals.

MANUFACTURED B\ 3AKER PERFORMANCE CHEMICAL INCORPORATED 3920 Essex Lane, Houston, Texas 77027

BD 05-93