



United States
Environmental Protection Agency
Washington, DC 20460

Registration
 Amendment
 Other

OPP Identifier Number
237070

Application for Pesticide - Section I

1. Company/Product Number 10707-33	2. EPA Product Manager M. Swindell (Acting)	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) MAGNACIDE B-615	PM# 31	
5. Name and Address of Applicant (Include ZIP Code) Baker Performance Chemicals, Incorporated 3920 Essex Lane Houston, TX 77027 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Product label is being submitted via notification per PR 93-10. The Environmental Hazards statement on the label has been updated accordingly. Certification is on attached cover letter.

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Metal Plastic Glass Paper Other (Specify) _____		
* Certification must be submitted	If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt No. per container			
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container	5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product		
6. Manner in Which Label is Affixed to Product		<input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled	<input type="checkbox"/> Other _____		

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Pat Gibson	Title Registration Specialist	Telephone No. (Include Area Code) 713/599-7507
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Registration Specialist	
4. Typed Name Pat Gibson	5. Date July 31, 1995	



MAGNACIDE® B-615

PRECAUTIONARY STATEMENTS

HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

DANGER: May cause severe eye damage and severe skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. May be harmful if inhaled, use only with adequate ventilation. May be harmful if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Extremely Flammable
Keep away from heat and flame.
Corrosive to metals.

STORAGE AND DISPOSAL

- PROHIBITIONS:** Do not contaminate water, food, or feed by storage or disposal.
- STORAGE:** This product is corrosive to mild steel. Do not store or transport in unlined metal containers.
- PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.
- CONTAINER DISPOSAL**
METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.
PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.
GENERAL: Consult federal, state or local disposal authorities for approved alternative procedures.

Controls slime-forming bacteria and sulfate reducing bacteria in oil field waters.

ACTIVE INGREDIENTS:	1-(Alkyl* amino)-3-aminopropane diacetate	46.87%
INERT INGREDIENTS:	53.13%
	TOTAL	100.00%

* Alkyl as in fatty acids of coconut oil.

KEEP OUT OF REACH OF CHILDREN DANGER

- INHALATION:** If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.
- EYE CONTACT:** In case of eye contact, immediately rinse with clean water for 20-30 minutes. Retract eyelids often. Obtain emergency medical attention.
- SKIN CONTACT:** Immediately remove contaminated clothing. Wash skin thoroughly with mild soap/water. Flush with lukewarm water for 15 minutes. If sticky, use waterless cleaner first. Obtain emergency medical attention.
- INGESTION:** If swallowed, give lukewarm water (pint) if victim is completely conscious/alert. DO NOT induce vomiting/risk of damage to lungs exceeds poisoning risk. Obtain emergency medical attention.

NOTE TO PHYSICIAN:
IF SWALLOWED, DO NOT INDUCE VOMITING. GASTRIC LAVAGE AND CATHARTIC INDICATED.
TREAT BURNS OR ALLERGIC REACTIONS CONVENTIONALLY AFTER DECONTAMINATION.

DISTRIBUTED BY
BAKER PERFORMANCE CHEMICALS, INC.
A DIVISION OF BAKER HUGHES
3920 ESSEX LANE, HOUSTON, TEXAS 77027
(713) 599-7400

EPA REGISTRATION NO.
10707-33

EPA ESTABLISHMENT NO.
10707-TX-003 L3 10707-OK-002 C3

EMERGENCY TELEPHONE (24 HOURS SERVICE) 713-599-7400

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

Dosages for recirculating water cooling towers or evaporative condensers will depend on the condition of the system before treatment. Heavily fouled systems should be cleaned first. Apply 120 to 500 ppm of MAGNACIDE® B-615 to the clean system when regrowth is first noticed. Repeat dosage one to three times per week until control is established. Add sufficient MAGNACIDE® B-615 to maintain 30-50 ppm in the blow-down water to keep the system under control. Always apply MAGNACIDE® B-615 to the system where it will be uniformly mixed.

OIL FIELD INJECTION WATERS

MAGNACIDE® B-615 may be used either in slug treatment or continuous application. Dosages may vary from 500 ppm of MAC B-615 in slug applications to 30-50 ppm of MAGNACIDE® B-615 in continuous treatment (1/4 pint per 1,000 gallons equals approx 30 ppm). A typical slug treatment is to add 120-500 ppm of B-615 (1 pint to 2 quarts per 1,000 gallons of water) to initially prevent growth of bacterial slime. Badly fouled systems may establish control followed by continuous treatment of 30-50 ppm (1/4 pint per 1,000 gallons of water) to maintain control. Monitoring test coupons and bacteria culture counts.

Notice of Warranty

Our recommendations for use of this product are based on the product being beyond the control of the manufacturer as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.

FLAM

BEST COPY AVAILABLE

M B M

MAGNACIDE® B-615

Controls slime-forming bacteria and sulfate reducing
bacteria in oil field waters

ACTIVE INGREDIENTS: 1-(Alkyl amino)-3-aminopropane
diacetate 46.87%

INERT INGREDIENTS: 53.13%
TOTAL 100.00%

Contains fatty acids of coconut oil.

KEEP OUT OF REACH OF CHILDREN DANGER

INHALATION: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

EYE CONTACT: In case of eye contact, immediately rinse with clean water for 20-30 minutes. Retract eyelids often. Obtain emergency medical attention.

SKIN CONTACT: Immediately remove contaminated clothing. Wash skin thoroughly with mild soap/water. Flush with lukewarm water for 15 minutes. If sticky, use waterless cleaner first. Obtain emergency medical attention.

INGESTION: If swallowed, give lukewarm water (pint) if victim is completely conscious/alert. DO NOT induce vomiting/risk of damage to lungs exceeds poisoning risk. Obtain emergency medical attention.

NOTE TO PHYSICIAN:

IF SWALLOWED, DO NOT INDUCE VOMITING. GASTRIC
LAVAGE AND CATHARTIC INDICATED.
TREAT BURNS OR ALLERGIC REACTIONS CONVENTIONAL-
LY AFTER DECONTAMINATION.

DISTRIBUTED BY

BAKER PERFORMANCE CHEMICALS, INC.
A DIVISION OF BAKER HUGHES
3920 ESSEX LANE, HOUSTON, TEXAS 77027
(713) 599-7400

REGISTRATION NO.
7-33

EPA ESTABLISHMENT NO.
10707-TX-003 ☐ 10707-OK-002 ☐

EMERGENCY TELEPHONE (24 HOURS OPERATING) 713-599-7400

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

Dosages for re-circulating water cooling towers or evaporative condensers will depend on the condition of the system before treatment. Heavily fouled systems should be cleaned first. Apply 120 to 500 ppma of MAGNACIDE® B-615 to the clean system when regrowth is first noticed. Repeat dosage one to three times per week until control is established. Add sufficient MAGNACIDE® B-615 to maintain 30-50 ppm in the blow-down water to keep the system under control. Always apply MAGNACIDE® B-615 to the system where it will be uniformly mixed.

OIL FIELD INJECTION WATERS

MAGNACIDE® B-615 may be used either in slug treatment or in continuous application. Dosages may vary from 500 ppm of MAGNACIDE® B-615 in slug applications to 30-50 ppm of MAGNACIDE® B-615 in continuous treatment (1/4 pint per 1,000 gallons equals approximately 30 ppm). A typical slug treatment is to add 120-500 ppm of MAGNACIDE® B-615 (1 pint to 2 quarts per 1,000 gallons of water) at intervals as needed to prevent growth of bacterial slime. Badly fouled systems may be slug treated to establish control followed by continuous treatment of 30-60 ppm (1/4 to 1/2 pints per 1,000 gallons of water) to maintain control. Monitoring methods include broth bottles, coupons and bacteria culture counts.

Notice of Warranty

Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.

Net Weights

5 gal/40 lbs. • 55 gal/439 lbs.
Available in Bulk Quantities.



BEST COPY AVAILABLE