

PM 33

SEP 23 1998

Baker Petrolite
3900 Essex Lane, 3rd floor
Houston, TX 77027


ATTENTION: Roberto F. Ceron
Registration Specialist--Chemical Registration Programs

SUBJECT: IPC 8915
EPA Registration Number: 10707-38
Your Notification Dated: August 14, 1998

This is to acknowledge receipt of your notification to add the alternate brand name "BPC 88915" to the product, "IPC 8915." This notification is acceptable and will be made part of the records for this file.

If you have any questions concerning this letter, please contact Barbara Mandula at (703) 308-7378.

Sincerely,



Marshall Swindell
Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510W)

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

EPA	United States Environmental Protection Agency Washington, DC 20460	<input type="checkbox"/> Registration <input checked="" type="checkbox"/> Amendment <input type="checkbox"/> Other	OPP Identifier Number
------------	--------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------	-----------------------

Application for Pesticide - Section I

1. Company/Product Number 10707-38	2. EPA Product Manager Velma Noble - M. S. JAMES	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) IPC 8915	PM# 31 33	
5. Name and Address of Applicant (Include ZIP Code) Baker Petrolite Corporation 3900 Essex La. Houston, TX 77027 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3)(b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For Section I and Section II.)


This notification amends the above registration to add the additional brand name:

BPC 68915

Section - III

1. Material This Product Will Be Packaged In:			
Child-Resistant Packaging <input type="checkbox"/> Yes* <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	2. Type of Container <input checked="" type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt No. per container
Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container None	5. Location of Label Directions <input checked="" type="checkbox"/> On Label <input type="checkbox"/> On Labeling accompanying product
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input checked="" type="checkbox"/> Other Pressure sensitive adhesive <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled			

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Roberto F. Ceron	Title Registration Specialist	Telephone No. (Include Area Code) 713-439-8293
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Registration Specialist	
4. Typed Name Roberto F. Ceron	5. Date 14 August 1998	



A Baker Hughes company

Controls bacteria, fungi, and algae in industrial recirculating water cooling towers; controls bacteria and fungi in metalworking fluids containing water; controls slime-forming bacteria and sulfate reducing bacteria in oil field waters; controls bacteria and fungal slime in paper mills; and controls bacteria, fungi, and algae in industrial air-washer systems.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%

INERT INGREDIENTS:	98.50%
TOTAL	100.00%

KEEP OUT OF REACH OF CHILDREN
DANGER
STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN:
Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

EPA REG. NO. 10707-38 **EPA EST. NO.** 10707-TX-007 707-PA-1
10707-CA-012 10707-OK-002

Manufactured by:
BAKER PETROLITE CORPORATION
3900 ESSEX LANE • HOUSTON, TEXAS 77027
Telephone (713) 599-7400
EMERGENCY TELEPHONE NUMBER (713) 599-7400

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER

CORROSIVE
CAUSES EYE DAMAGE AND SKIN BURNS.
MAY CAUSE ALLERGIC SKIN REACTION.
MAY BE HARMFUL IF INHALED.
MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.

Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of wastes.

STORAGE AND DISPOSAL

1. STORAGE
Keep container closed when not in use. Leaking drums should be placed in overpack drums for disposal. Use absorbent material such as clay or diatomaceous earth to clean up all spills and dispose of in an approved disposal site. Do not stack drums more than four (4) high. BPC 68915 is corrosive to mild steel and brass. Handling equipment should be made of 316SS. Polyethylene Polypropylene.

2. PROHIBITIONS
Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

3. PESTICIDE DISPOSAL
Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

4. CONTAINER DISPOSAL
Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

5. GENERAL
Consult Federal, State or Local authorities for approved alternative procedures.

BPC 68915

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae and fungi, add BPC 68915 to the tower basin, distribution box or some other point to insure uniform mixing.

INITIAL DOSE: When the system is noticeably fouled, apply 1.26 to 7.46 pounds (19 to 113 fluid ounces) of BPC 68915 per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.3 to 1.86 pounds (4.55 to 28 fluid ounces) of BPC 68915 per 1000 gallons of water in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

METALWORKING FLUIDS CONTAINING WATER

TREATMENT:
BPC 68915 is recommended for the control of bacteria and fungi in soluble and emulsifiable type aqueous metalworking fluids such as emulsified petroleum oils, and formulations containing alcoholic fatty acid sulfonated red oil, or naphthalene sulfonate. These fluids are usually prepared by diluting the product concentrates 1:40 to 1:60 with water.

For the maintenance of a nonfouled system use BPC 68915 at 32 fluid ounces per 1000 gallons of emulsion (2 pounds) every 4 weeks or 32 to 154 fluid ounces per 1000 gallons emulsion (2 to 10 pounds) every 8 to 12 weeks. For a noticeable fouled system use an initial dose of 64 to 154 fluid ounces per 1000 gallons emulsion (4 to 10 pounds) to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed into the use dilution of the metalworking fluid using a metering pump.

OIL FIELD INJECTION WATERS

For the control of slime forming bacteria and sulfate reducing bacteria in oil field waters, slug treat with 67 to 332 ppm BPC 68915 depending on the severity of contamination.

INITIAL DOSE: Add 166 to 332 ppm pounds BPC 68915 per 1000 barrels of water, thoroughly mixed. Repeat treatment after the following.

SUBSEQUENT DOSE: Add 67 to 166 ppm BPC 68915 per 1000 barrels of water.

TREATMENT:
BPC 68915 is recommended for the control of bacteria and fungi in water used in the production of paper.

POINT OF ADDITION: BPC 68915 should be added to the water before mixing such as the Beater, Hydro, or other point.

DOSAGE: Apply 0.44 to 1.5 pounds (7 to 28 fluid ounces) of pulp or paper produced as a slug should be cleaned before initial treatment.

AIR-WASHER SYSTEMS

Add to the air washer sump or chill water. BPC 68915 (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of water in the system) depending upon the nature and severity of fungi and algae which cause fouling in the system.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 1.26 to 7.46 pounds or 19 to 113 fluid ounces (the system.) Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.3 to 1.86 pounds or 4.5 to 28 fluid ounces weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 1.26 to 7.46 pounds or 19 to 113 fluid ounces (the system.)

SUBSEQUENT DOSE: Maintain this treatment level (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces up water).

Badly fouled systems must be cleaned before treatment is begun.

NOTE: For use only in industrial air washer systems.

NOTICE: Seller warrants that the product is reasonably fit for the purpose stated on the label under normal conditions of use, but does not warrant the suitability or fitness for a particular application or handling of this product in a manner other than that stated under abnormal conditions, or under conditions where the buyer assumes the risk of any such use.

Net Weight
55