

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460



United States
Environmental Protection
Agency

Office of Pesticide Programs

Baker Petrolite Corporation
12645 West Airport Blvd
Sugar Land, TX 77478

APR 20 2010

Attention: Kenneth J. Medeiros
Senior Regulatory Specialist

Subject: X-CIDE 620
EPA Registration No. 10707-38
Notifications Dated April 5, 2010

This will acknowledge receipt of your notification, submitted under the provisions of FIFRA Section 3(c)(9).

Proposed Notification

- Label Change per PR Notice 2007-4

General Comment

Based on a review of the submitted material, the following comments apply:

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been made a part of your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

A handwritten signature in black ink, appearing to read "M Swindell".

Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510P)



Please read instructions on reverse before completing form.

Form Approved. OMB No. 2070-0060

| | | |
|--|--|-----------------------------|
| <p>United States Environmental Protection Agency Washington, DC 20460</p> | <input type="checkbox"/> Registration <input type="checkbox"/> Amendment <input checked="" type="checkbox"/> Other | OPP Identifier Number _____ |
|--|--|-----------------------------|

Application for Pesticide - Section I

| | | |
|---|---|---|
| 1. Company/Product Number: 10707-38 | 2. EPA Product Manager: Marshall Swindell | 3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted |
| 4. Company/Product (Name): X-CIDE 620 Industrial Microbiocide | PM#: 33 | |
| 5. Name and Address of Applicant (Include ZIP Code): Baker Petrolite Corporation 12645 West Airport Blvd. Sugar Land, TX 77478 <input type="checkbox"/> Check if this is a new address | | 6. Expedited Review: In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____ |

Section - II

| | |
|--|---|
| <input type="checkbox"/> Amendment - Explain below. <input type="checkbox"/> Resubmission in response to Agency letter dated _____ <input checked="" type="checkbox"/> Notification - Explain below. | <input type="checkbox"/> Final printed labels in response to Agency letter dated _____ <input type="checkbox"/> "Me Too" Application. <input type="checkbox"/> Other - Explain below: |
|--|---|

Explanation: Use additional page(s) if necessary. (For section I and Section II.):

Notification of label change per PR Notice 2007-4. This notification is consistent with the guidance in PR Notice 2007-4 and the requirements of EPA's regulations at 40 CFR §§ 156.10, 156.140, 156.144, 156.146, and 156.156. No other changes have been made to the labeling or the Confidential Statement of Formula for this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willingly make any false statements to EPA. I further understand that if the amended label is not consistent with the requirements of 40 CFR §§ 156.10, 156.140, 156.144, 156.146, and 156.156, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

Section - III

| | | | | | |
|--|---|--|--|---|--|
| 1. Material This Product Will Be Packaged In: | | | | 2. Type of Container: | |
| Child-Resistant Packaging: <input type="checkbox"/> Yes <input type="checkbox"/> No | Unit Packaging: <input type="checkbox"/> Yes <input type="checkbox"/> No | Water Soluble Packaging: <input type="checkbox"/> Yes <input type="checkbox"/> No | | | <input type="checkbox"/> Metal <input type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____ |
| <i>* Certification must be submitted</i> | | If "Yes" Unit Packaging wgt. No. per container | If "Yes" Package wgt No. per container | | |
| 3. Location of Net Contents Information: <input type="checkbox"/> Label <input type="checkbox"/> Container | | 4. Size(s) Retail Container: | | 5. Location of Label Directions: <input type="checkbox"/> _____ | |
| 6. Manner in Which Label is Affixed to Product | | | <input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled <input type="checkbox"/> Other _____ | | |

Section - IV

| | | |
|--|---|---|
| 1. Contact Point. (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.) | | |
| Name: Kenneth J. Medeiros | Title: Sr. Registration Specialist | Telephone No. (Include Area Code): 281-275-7205 |
| Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law. | | 6. Date Application Received: <div style="text-align: center; border: 1px solid black; padding: 5px;">(Stamped)</div> |
| 2. Signature: | 3. Title: Sr. Registration Specialist | |
| 4. Typed Name: Kenneth J. Medeiros | 5. Date: April 5, 2010 | |



Baker Petrolite

12645 West Airport Blvd.
Sugar Land, Texas 77478
P.O. Box 5050
Sugar Land, Texas 77487-5050
Tel 281-276-5400
Fax 281-275-7385

April 5, 2010

Document Processing Desk (NOTIF)
Office of Pesticide Programs (7504P)
U.S. Environmental Protection Agency
1200 Pennsylvania Avenue, N.W.
Washington, DC 20460

Subject: Notification of Revised Container Disposal Statements per PR Notice 2007-4 for
X-CIDE 620 Industrial Microbiocide (EPA Reg. No. 10707-38).

Dear Madam/Sir:

Enclosed are the following documents necessary for notification of the revised label for the
above subject product, per PR Notice 2007-4.

- EPA Form 8570-1 *Application for Pesticide*
- A copy of the product label with the changes marked.

Please feel free to contact me if you have any questions. I can be reached by phone at
281-275-7205 or email at ken.medeiros@bakerhughes.com.

Sincerely,

Kenneth J. Medeiros
Sr. Registration Specialist

| | |
|---------|---------|
| cccccc | cccc |
| c c c c | c |
| c c c c | |
| c c c c | |
| c c c c | cccccc |
| c c c c | c c c c |
| c c c c | c |
| c c c c | cccccc |
| c c c c | c c c c |
| c c c c | c c c c |

PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS DANGER

CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS. MAY BE FATAL IF ABSORBED THROUGH SKIN. MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL IF INHALED OR SWALLOWED. Do not get in eyes, on skin or on clothing. Mixers, loaders and others exposed to this product must wear long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separate from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly. This product may cause skin sensitization reactions in some people.

ENVIRONMENTAL HAZARDS

This chemical is toxic to terrestrial and aquatic plants, fish and aquatic invertebrates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
Do not apply this product in a way that will contact workers or other persons.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

For the control of bacteria, algae and fungi, add X-CIDE 620 Industrial Microbiocide to the lower basin, distribution box or some other point to insure uniform mixing.
INITIAL DOSE: When the system is noticeably fouled, apply 1.26 to 7.46 pounds (19 to 113 fluid ounces) of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system. Repeat until control is achieved.
SUBSEQUENT DOSE: When microbial control is evident, add 0.3 to 1.86 pounds (4.55 to 28 fluid ounces) of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

METALWORKING FLUIDS CONTAINING WATER

TREATMENT:
X-CIDE 620 Industrial Microbiocide is recommended for the control of bacteria and fungi in soluble and emulsifiable type aqueous metalworking fluids such as emulsified petroleum oils and formulations containing triethanolamine, fatty acid sulfonated red oil or naphthalene sulfonate. These fluids are usually prepared by diluting the product concentrates 1:40 to 1:60 with water.

NET WEIGHT: Drum, Bulk, or As Marked on Container

Rev. 03/10

X-CIDE® 620

Controls bacteria, fungi and algae in industrial recirculating water cooling towers; controls bacteria and fungi in metal working fluids containing water; controls slime-forming bacteria and sulfate-reducing bacteria in oil field waters; controls bacteria and fungal slime in paper mills; controls bacteria, fungi and algae in industrial air-washer systems. The following end uses are excluded in California: controls bacteria and fungi in ultra filtration units and non-medical/non-potable reverse osmosis systems.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one..... 1.11%
2-Methyl-4-isothiazolin-3-one..... 0.39%

INERT INGREDIENTS:

..... 98.50%

TOTAL..... 100.00%

Product contains 0.27 pounds active ingredients per gallon.

KEEP OUT OF REACH OF CHILDREN DANGER

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

| FIRST AID | |
|---|--|
| Call poison control center or doctor immediately for treatment advice. Have the product container or label with you when calling a poison control center, doctor, or going for treatment. | |
| IF ON SKIN OR CLOTHING | <ul style="list-style-type: none"> Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. |
| IF IN EYES | <ul style="list-style-type: none"> Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after 5 minutes, then continue rinsing eye. |
| IF INHALED | <ul style="list-style-type: none"> Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. |
| IF SWALLOWED | <ul style="list-style-type: none"> Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. |

Note to physician: Probably mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

EPA Registration Number.....10707-38
EPA Establishment Numbers.....10707-TX-003, 10707-LA-001, 10707-CA-012, 10707-PA-001, 10707-MS-001

BAKER PETROLITE CORPORATION
12645 WEST AIRPORT BLVD.
SUGAR LAND, TX 77478

EMERGENCY CONTACT (24 HOURS PER DAY): 800-231-3606

Read Product Material Safety Data Sheet prior to use. PRODUCT WARRANTY, DISCLAIMER AND LIMITATION OF LIABILITY ARE FOUND THEREON. Use of Product signifies agreement with these provisions.

DIRECTIONS FOR USE

For the maintenance of a non fouled system, use X-CIDE 620 Industrial Microbiocide at 32 fluid ounces per 1,000 gallons of emulsion (2 pounds) every 4 weeks or 32 to 154 fluid ounces per 1,000 gallons emulsion (2 to 10 pounds) every 8 to 12 weeks. For a noticeably fouled system, use an initial dose of 64 to 154 fluid ounces per 1,000 gallons emulsion (4 to 10 pounds) to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the use dilution of the metalworking fluid using a metering pump.

OIL FIELD INJECTION WATERS

For the control of slime-forming bacteria and sulfate-reducing bacteria in oil field waters, slug treat with 67 to 332 ppm X-CIDE 620 Industrial Microbiocide depending on the severity of contamination.
INITIAL DOSE: Add 166 to 332 ppm X-CIDE 620 Industrial Microbiocide (6.9 to 13.9 gallons or 58.0 to 116.8 pounds X-CIDE 620 Industrial Microbiocide per 1,000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.
SUBSEQUENT DOSE: Add 67 to 166 ppm X-CIDE 620 Industrial Microbiocide (2.8 to 6.9 gallons or 23.5 to 58.0 X-CIDE 620 Industrial Microbiocide per 1,000 barrels of water) every seven days or as needed to maintain control.

PAPER MILLS

TREATMENT: X-CIDE 620 Industrial Microbiocide is recommended for the control of bacterial and fungal slime in the production of paper.
POINT OF ADDITION: X-CIDE 620 Industrial Microbiocide should be added to a point in the system to insure uniform mixing such as the Beater, Hydropulper or Pan or Broke Storage Pumps.
DOSAGE: Apply 0.44 to 1.5 pounds (7 to 23 fluid ounces) of X-CIDE 620 Industrial Microbiocide per ton (dry basis) of pulp or paper produced as a slug dose. If needed, repeat daily. Badly fouled systems should be cleaned before initial treatment.

AIR-WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 35 to 883 ppm X-CIDE 620 Industrial Microbiocide (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces) of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system) depending upon severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.
INTERMITTENT OR SLUG METHOD
INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm X-CIDE 620 Industrial Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm X-CIDE 620 Industrial Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of X-CIDE 620 per 1,000 gallons of water) weekly or as needed to maintain control.
CONTINUOUS FEED METHOD
INITIAL DOSE: When the system is just noticeably fouled, apply 148 to 883 ppm X-CIDE 620 Industrial Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system).

Do not reuse the disposal is the re-refilling is the re-empt the remain Fill the containe with the pump fo collection system

SUBSEQUENT I 219 ppm (0.3 Microbiocide per Badly fouled sys NOTE: For use eliminating cont

ULTRA F

X-CIDE 620 In ultra filtration X-CIDE 620 Ind Add 10 to 332 ingredient) into l feed or periodic reverse osmosis For the control Industrial Micro feed. For periodic Microbiocide to Badly fouled sys

PHYSICAL ANI store or transpo PESTICIDE STI cleaning of equi PESTICIDE DIS excess pesticid disposed of by environmental c regional office k

Text for non-reli CONTAINER DI Offer for recycli employing.

For containers o into applicatio drip. Fill the co into applicatio for 10 seconds

For containers w remaining conte water. Replace ensur at least and tip it back a mix tank or sto

Text for refillab CONTAINER DI Do not reuse the disposal is the re-refilling is the re-empt the remain Fill the containe with the pump fo collection system

Lea la hoja de datos de seguridad de materiales del producto antes de usarlo. LA GARANT RESPONSABILIDAD SE ENCUENTRAN EN DICHOS DOCUMENTOS. El uso del product

X-CIDE® 620

Controls bacteria, fungi and algae in industrial recirculating water cooling towers; controls bacteria and fungi in metal working fluids containing water; controls slime-forming bacteria and sulfate-reducing bacteria in oil field waters; controls bacteria and fungal slime in paper mills; controls bacteria, fungi and algae in industrial air-washer systems. The following end uses are excluded in California: controls bacteria and fungi in ultra filtration units and non-medical/non-potable reverse osmosis systems.

ACTIVE INGREDIENTS:
 5-Chloro-2-methyl-4-isothiazolin-3-one 1.11%
 2-Methyl-4-isothiazolin-3-one 0.39%

INERT INGREDIENTS:
 TOTAL: 98.50%

Product contains 0.27 pounds active ingredients per gallon.

KEEP OUT OF REACH OF CHILDREN
DANGER

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

| | |
|--|--|
| FIRST AID | |
| Call poison control center or doctor immediately for treatment advice. Have the product container or label with you when calling a poison control center doctor, or going for treatment. | |
| IF ON SKIN OR CLOTHING | <ul style="list-style-type: none"> Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. |
| IF IN EYES | <ul style="list-style-type: none"> Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after 5 minutes, then continue rinsing eye. |
| IF INHALED | <ul style="list-style-type: none"> Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. |
| IF SWALLOWED | <ul style="list-style-type: none"> Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. |

Note to physician: Probably mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

EPA Registration Number 10707-38
 EPA Establishment Numbers 10707-TX-003, 10707-LA-001, 10707-CA-012, 10707-PA-001, 10707-MS-001

BAKER PETROLITE CORPORATION
 12645 WEST AIRPORT BLVD.
 SUGAR LAND, TX 77478

EMERGENCY CONTACT (24 HOURS PER DAY): 800-231-3606

DIRECTIONS FOR USE

For the maintenance of a non fouled system, use X-CIDE 620 Industrial Microbiocide at 32 fluid ounces per 1,000 gallons of emulsion (2 pounds) every 4 weeks or 32 to 154 fluid ounces per 1,000 gallons emulsion (2 to 10 pounds) every 8 to 12 weeks. For a noticeably fouled system, use an initial dose of 64 to 154 fluid ounces per 1,000 gallons emulsion (4 to 10 pounds) to be followed by subsequent maintenance dosages depending upon the treatment interval noted above. A higher dosage range and/or increased frequency of treatment may be required depending upon rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc. The preservative should be dispensed into the use dilution of the metalworking fluid using a metering pump.

OIL FIELD INJECTION WATERS

For the control of slime-forming bacteria and sulfate-reducing bacteria in oil field waters, slug treat with 67 to 332 ppm X-CIDE 620 Industrial Microbiocide depending on the severity of contamination.
INITIAL DOSE: Add 166 to 332 ppm X-CIDE 620 Industrial Microbiocide (6.9 to 13.9 gallons or 58.0 to 116.8 pounds X-CIDE 620 Industrial Microbiocide per 1,000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.
SUBSEQUENT DOSE: Add 67 to 166 ppm X-CIDE 620 Industrial Microbiocide (2.8 to 6.9 gallons or 23.5 to 58.0 X-CIDE 620 Industrial Microbiocide per 1,000 barrels of water) every seven days or as needed to maintain control.

PAPER MILLS

TREATMENT: X-CIDE 620 Industrial Microbiocide is recommended for the control of bacterial and fungal slime in the production of paper.
POINT OF ADDITION: X-CIDE 620 Industrial Microbiocide should be added to a point in the system to insure uniform mixing such as the Beater, Hydropulper or Pan or Broke Storage Pumps.
DOSAGE: Apply 0.44 to 1.5 pounds (7 to 23 fluid ounces) of X-CIDE 620 Industrial Microbiocide per ton (dry basis) of pulp or paper produced as a slug dose, if needed, repeat daily. Badly fouled systems should be cleaned before initial control is achieved.

AIR-WASHER SYSTEMS

Add to the air washer sump or chill water sump to insure uniform mixing, 35 to 883 ppm X-CIDE 620 Industrial Microbiocide (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system) depending upon severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.
INTERMITTENT OR SLUG METHOD
INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm X-CIDE 620 Industrial Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system). Repeat until control is achieved.
SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm X-CIDE 620 Industrial Microbiocide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of X-CIDE 620 per 1,000 gallons of water) weekly or as needed to maintain control.
CONTINUOUS FEED METHOD
INITIAL DOSE: When the system is just noticeably fouled, apply 148 to 883 ppm X-CIDE 620 Industrial Microbiocide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of water in the system).

DIRECTIONS FOR USE

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of X-CIDE 620 Industrial Microbiocide per 1,000 gallons of makeup water).
NOTE: For use only in industrial air washing systems that maintain effective mist eliminating components.

ULTRA FILTRATION UNITS AND NON-MEDICAL/NON-POTABLE REVERSE OSMOSIS SYSTEMS NOT FOR USE IN THE STATE OF CALIFORNIA

X-CIDE 620 Industrial Microbiocide is recommended for the control of bacteria and fungi in ultra filtration units and non-medical/non-potable reverse osmosis systems. Use of X-CIDE 620 Industrial Microbiocide in potable water or dialysis is prohibited.
 Add 10 to 333 ppm of X-CIDE 620 Industrial Microbiocide (0.15 to 5 ppm ingredient) into industrial ultra filtration or reverse osmosis systems by either continuous feed or periodic injection. Compatibility of X-CIDE 620 Industrial Microbiocide with reverse osmosis membranes should be confirmed with membrane manufacturers.
 For the control of bacteria and fungi in carbon beds, add 10 to 333 ppm X-CIDE 620 Industrial Microbiocide (0.15 to 5 ppm active ingredient) by either continuous or batch feed.
 For periodic membrane cleaning, add 0.4 to 1.0 pound of X-CIDE 620 Industrial Microbiocide to every 120 gallons of cleaning solution (6 to 15 ppm active ingredient). Badly fouled systems should be cleaned before treatment is begun.

STORAGE AND DISPOSAL

PHYSICAL AND CHEMICAL HAZARDS: This product is corrosive to mild steel. Do not store or transport in unlined metal containers.
PESTICIDE STORAGE: Do not contaminate water, food or feed by storage, disposal or cleaning of equipment.
PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or insecticide is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your state pesticide or environmental control agency or the hazardous waste representative at the nearest EPA regional office for guidance.

Text for non-refillable containers
CONTAINER DISPOSAL: Non-refillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.
For containers of 5 gallons or less: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.
For containers with capacities greater than 5 gallons: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.
Text for refillable containers
CONTAINER DISPOSAL: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times.