

ACCEPTED

SEP 08 1998

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 10707-44

X-CIDE® 207

EMERGENCY TELEPHONE NUMBERS

CHEMTREC: 800-424-9300
CANUTEC: 613-996-6666
CUSTOMER CARE: 800-231-3606

Baker Petrolite Corp
3900 Essex Lane
Houston, TX 77027-5133 U.S.A.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER: Corrosive. Harmful or fatal if swallowed. Vapor harmful. Avoid breathing spray mist or vapors. Do not get on skin. Causes eye damage and skin irritations. Do not get in eyes or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PRACTICAL TREATMENT STATEMENTS

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. If inhaled, remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

Read Product Material Safety Data Sheet prior to use. PRODUCT WARRANTY, DISCLAIMER AND LIMITATION OF LIABILITY ARE FOUND THEREON. Use of Product signifies agreement with these provisions.

Lea la hoja de datos de seguridad de materiales del producto antes de usarlo. LA GARANTIA DEL PRODUCTO, EL DESCARGO Y LA LIMITACION DE RESPONSABILIDAD SE ENCUENTRAN EN DICHS DOCUMENTOS. El uso del producto significa acuerdo con estas disposiciones.

X-CIDE® 207

Industrial Microbiocide

FOR USE IN INDUSTRIAL PROCESSES ONLY. NOT FOR DOMESTIC USE.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one . . . 5.36%
2-Methyl-4-isothiazolin-3-one 1.62%

INERT INGREDIENTS: 93.02%

100.00%

KEEP OUT OF REACH OF CHILDREN
DANGER

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA REG. NO. 10707-44
EPA EST. NO. 10707-TX-008

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

RECOMMENDED USES

OILFIELD WATERS:
X-CIDE 207 Industrial Microbiocide is used for the control of slime forming bacteria and sulfate reducing bacteria in oilfield waters.

Treatment: Slug treat with 15-75 ppm X-CIDE 207 Industrial Microbiocide depending on the severity of contamination. X-CIDE 207 Industrial Microbiocide can be used in stagnant areas such as storage tanks, sumps and pits. Add 35-75 ppm X-CIDE 207 Industrial Microbiocide (8.2-17.6 pounds X-CIDE 207 Industrial Microbiocide per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

DRILLING MUDS AND WORKOVER OR COMPLETION FLUIDS:
X-CIDE 207 Industrial Microbiocide is effective in controlling bacteria and fungi in water based drilling muds.

Treatment: X-CIDE 207 Industrial Microbiocide should be added at 25-500 ppm through the mud hopper or at the pump suction. A typical 50 ppm treatment is 1.75 pounds per 100 barrels into the drilling mud circulating system.

WELL STIMULATION AND FRACTURING:
X-CIDE 207 Industrial Microbiocide is effective in controlling fungi and bacteria in guar gum based fracturing fluid systems.

Treatment: X-CIDE 207 Industrial Microbiocide should be added to the storage tanks at 25-500 ppm and circulated. For example, a 50 ppm treatment is 8.75 pounds per 500 barrel fracturing tank.

Affix Corrosive (8) label

207-4-98

PM 31

10707-44

4/8/98

Page 1 of 2

STORAGE AND DISPOSAL

PROHIBITIONS: This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

ONE-GALLON PLASTIC BOTTLES: Do not reuse empty one-gallon plastic containers. Wrap container and put in trash.

GENERAL: Consult federal, state or local disposal authorities for approved alternative procedures.

3 LBS. NET WEIGHT

Corrosive Solid, Toxic, n.o.s.(contains 5-Chloro-2-Methyl-4-Isothiazolin-3-One) UN2923