707 - 404

4-8-2004

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

APR 0 8 2004

Baker Petrolite Corporation 12645 West Airport Blvd. Sugar Land, TX 77478

Attention: Miles R. Rhea Senior Manager

Subject: X-CIDE 207 EPA Registration No. 10707-44 E-Mail Letter Dated March 23, 2004

The labeling, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable.

- Basic Confidential Statement of Formula (CSF)

- Revised product labeling

General Comments

The revised Basic CSF dated October 27, 2003 is in compliance with PR Notice 92-1, agrees with the label and is acceptable.

A stamped copy of the accepted labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,

Marshall Swindell Product Manager 33 Regulatory Management Branch 1 Antimicrobial Division (7510C)

Enclosure

CONCURRENCES

SYMBOL

BJRNAME
DATE

CONCURRENCES

OFFICIAL FILE COP

PRECAUTIONARY STATEMENTS HAZARD TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Harmful or fatal if swallowed. Vapor harmful. Avoid breathing spray mist or vapors. Do not get on skin. Causes eye damage and skin irritations. Do not get in eyes or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, Estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE Open dumping is prohibited. Store only in original container. Do not reuse empty container. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL (Larger 1 gal.) Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. In addition, plastic containers may be disposed of by incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

X-CIDE[®] 207

INDUSTRIAL MICROBIOCIDE

FOR USE IN INDUSTRIAL PROCESSES ONLY. NOT FOR DOMESTIC USE.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	4.99%
2-Methyl-4-isothiazolin-3-one	
INERT INGREDIENTS:	<u>93.23%</u>
TOTAL:	100.00

KEEP OUT OF REACH OF CHILDREN DANGER/PELIGRO

FIRST AID
Call poison control center or doctor immediately for treatment advice.
Have the product container or label with you when calling a poison control
center doctor, or going for treatment.

IF ON SKIN OR CLOTHING	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.
IF IN EYES	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
IF SWALLOWED	 Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
IF INHALED	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.

NOTE TO PHYSICIAN : Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

EPA Registration Number......10707-44 ACCEPTED DISTRIBUTED BY: **BAKER PETROLITE CORPORATION** APR 0 8 2004 12645 WEST AIRPORT BLVD. SUGAR LAND, TX 77478 Under the Federal Insecticide, Funcicide, and Rodenticide CHIEROSENCY CONTACT (24 HOURS PER DAY): 800-231-3606 EPA Reg. No. 18 707-44

()

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its label.

RECOMMENDED USES OIL FIELD WATERS:

X-CIDE[®] 207 Industrial Microbiocide is used for the control of slime forming bacteria and sulfate reducing bacteria in oilfield waters.

Treatment: Slug treat with 15-75 ppm X-CIDE® 207 Industrial Microbiocide depending on the severity of contamination. X-CIDE® 207 Industrial Microbiocide can be used in stagnant areas such as storage tanks, sumps and pits. Add 35-75 ppm X-CIDE® 207 Industrial (8.2 ~ 17.6 pounds X-CIDE® 207 Industrial Microbiocide per 1000 barrels of water) at a point in the system where it will be uniformly mixed. Repeat treatment after three days or as needed until control is achieved.

DRILLING MUDS AND WORKOVER OR COMPLETION FLUIDS:


X-CIDE[®] 207 Industrial Microbiocide is effective in controlling bacteria and fungi in water based drilling muds.

Treatment: X-CIDE® 207 Industrial Microbiocide should be added at 25-500 ppm through the mud hopper or at the pump suction. A typical 50 ppm treatment is 1.75 pounds per 100 barrels into the drilling mud circulating system.

WELL STIMULATION AND FRACTURING:

X-CIDE[®] 207 Industrial Microbiocide is effective in controlling fungi and bacteria in guar gum based fracturing fluid systems.

Treatment: X-CIDE® 207 Industrial Microblocide should be added to the storage tanks at 25-500 ppm and circulated. For example, a 50 ppm treatment is 8.75 pounds per 500 barrels fracturing tank.



Net Contents: Drum, Bulk, or As Marked On Container

6 lbs NET WEIGHT

REV 10/03