Seal Sosote

reserving pound ARK)

. NO. 10727-2 IMENT NO. 10727-PA-1

OR F. SWALLOWED. ck/side panel.

NIKA IES

IP, PA. 19442

BALLON

This product compliment Regulation Viment of Public Control Beard.

GUARDSEAL CREOSOTE WOOD PRESERVING COMPOUND

GUARDSEAL CREOSOTE WOOD PRESERVING CUMPOUND adds years of life to lumber. It saves time, labor, and money, repelling wood-destroying termites, and insects. It preserves wood exposed to moisture above or below ground. GUARDSEAL CREOSOTE WOOD PRESERVING COMPOUND a pure distillate of high temperature Coal Tar processed for reduction of freezing point. It is used on fence posts, sills, joists, and wood in contact with the ground. For best results use two coats on wood which is to be in contact with soil. GUARDSEAL CREOSOTE WOOD PRESERVING COMPOUND is not suitable for application to surfaces that are to be painted. It stains the wood a rich brown color. Do not use inside dairy barns, silos, or other structures where it may contact food, feed, or livestock.

Work area should be well ventilated. Wood should be dry and well seasoned. Use Creosote only when temperature is above 60 degrees F. This product will crystallize under 40 degrees F. To liquefy — place cans in a warm area until ready for use. This product should be stored in areas above 45° for all times.

Brush Application -- Apply two coats, using good quality brushes. Apply generously around ends, knots, and checked places. Covers approximately 100-, and square feet per gallon, depending upon conditions of surface.

Spray — Apply two coats. Covers approximately 100-150 square feet per gallon, first coat, and 150-225 square feet per gallon, second coat.

Dipping — Completely immerse timber. Protect oil from sparks and open flames. Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and well-seasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver.

General:

Do not use empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning or disposal of wastes. Apply this product only as specified on this label.

Creosoted wood should not be used where its odor can contaminate food products. Keep container tightly closed when not in use.