

# ipco

ACTIVE INGREDIENT:  
ALKYL (50% C12, 30% C14, 17% C16, 3% C18)  
DIMETHYL ETHYLBENZYL AMMONIUM  
CYCLOHEXYLSULFAMATE..... 0.72%  
INERT INGREDIENTS..... 99.28%  
100.00%

EPA Reg. No. 10751-2

# VINYL LATEX HOSPITAL PAINT

## 600-A WHITE

ACCEPTED  
Feb-10-1972  
UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
UNDER NO. 10751-2

NET: U.S. GALS.

**WARNING!**  
KEEP OUT OF REACH OF CHILDREN. SEE WARNING STATEMENTS ON BACK PANEL.

LOW LUSTRE LATEX

BACTERIOSTATIC

FAST DRYING

SCRUBBABLE

ODORLESS

DURABLE

**ipco**

ACTIVE INGREDIENT:  
ALKYL (50% C<sub>12</sub>, 30% C<sub>14</sub>, 17% C<sub>16</sub>, 3% C<sub>18</sub>)  
DIMETHYL ETHYLBENZYL AMMONIUM  
CYCLOHEXYLSULFAMATE..... 0.72%  
INERT INGREDIENTS..... 99.28%  
100.00%

EPA Reg. No. 10751-2

**VINYL LATEX  
HOSPITAL PAINT**

**600-A WHITE**

ACCEPTED  
Feb-10-1977  
UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
UNDER NO. 10751-2

NET: U.S. GALS.

**WARNING!**

KEEP OUT OF REACH OF CHILDREN. SEE WARNING STATEMENTS ON BACK PANEL.

## IPCO LOW-LUSTRE LATEX ENAMEL

IPCO LOW-LUSTRE provides the quick, easy way to obtain a smooth, uniform low-lustre finish on interior surfaces without muss, fuss or long clean-ups. It may be used on plaster and other forms of masonry, on primed or previously painted wood and metal, as well as on wallboard. Dries within the hour.

### DIRECTIONS FOR USE.

Surfaces to be painted must be free of grease, wax, dust, or powdery paint. Glossy surfaces should be lightly sand-papered to permit adhesion of the top coat of paint. Mix well by stick or shaker.

A nylon brush is recommended, — and painting is best accomplished with a minimum of cross-brushing. Spackled cracks and plaster patches may be spot primed as soon as they are dry, and repainted in a matter of minutes.

For two coat jobs, a second coat of Low-Lustre enamel after 1 hour of application of the first coat would give an excellent job.

For re-coat work over walls afflicted with mildew, wash walls with a straight solution of vinegar, then proceed with re-coat work.

Very porous uncoated plaster or concrete surfaces may be dampened with water just prior to being painted. The paint itself is ready to be used with no thinning.

While painting, keep a wet cloth or sponge handy to wipe up any accidental spatters before they dry. As soon as possible after painting, wash brushes, rollers, etc., with warm soapy water.

When dry, the Low-Lustre finish resists penetration by stains, dirt, moisture or bacteria. Most discolorations are easily removed by sponge dipped in soapy water or in mild detergent solution. Stubborn grease marks may be removed by solvents such as naphtha, using very light strokes of the sponge, followed by flushing with soap and water.

**CAUTION:** Do not mix this paint with other paints or paint products, thinners or colors except Universal Tinting Colors. Do not apply over glue size or other water-soluble materials, or over wallpaper with soluble dyes. Protect from freezing. For absolute uniformity of color, where more than one can of a color is to be used, combine and mix together all of the paint of that particular color before proceeding with the job.

38-135

EPA Reg. No. 10751-2

**WARNING:** — HARMFUL OR FATAL IF SWALLOWED. Do not apply on toys, furniture or interior surfaces which might be chewed by children. Avoid contact with skin or breathing of spray mist. Close container after each use. Do not take internally. Not for use or storage in or around the home environment.

Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

Distributed by

**IPCO HOSPITAL SUPPLY CORP.**

GENERAL OFFICES: NEW YORK, N.Y. 10013

ACCEPTED

Feb-10-1973

UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC PESTS, REGISTERED  
UNDER NO. 10751-2