



421A



Professional Industrial & Institutional Products

Contract WASP & HORNET KILLER II

Dielectric breakdown voltage in accordance with ASTM D 877: No breakdown to 20,000 volts.

A SPRAY FROM 10 FEET OR MORE AWAY DIRECTED INTO NESTS, CREVICES, HOLES WILL KILL WASPS, HORNETS, BEES, YELLOW JACKETS.

Precautionary Statements • Hazards to Humans and Domestic Animals

CAUTION: Do not use in commercial food processing, preparation, serving or storage areas. In the home all food processing surfaces and utensils should be covered during treatment or thoroughly washed before use. Cover exposed food.

Remove pets, birds and cover fish aquariums before spraying.

Statement of Practical Treatment	
IF SWALLOWED:	Do not induce vomiting because of aspiration hazard. Get medical attention.
IF ON SKIN:	Wash off with soap and water. Get medical attention if irritation persists.
IF IN EYES:	Flush with plenty of water. Get medical attention if irritation persists.

Physical Hazards.

FLAMMABLE. Contents under Pressure. Keep away from heat, sparks and open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Control of Wasps, Hornets, Bees, Yellow Jackets: Point valve opening toward nest, crevice or hold where infestation or insects are known to be inside. Depress button, continuing to spray until the nest or the area sprayed is completely saturated. Application at night after the insects have returned to their nest is preferable. Repeat as necessary.

STORAGE AND DISPOSAL

STORAGE: Store in a cool area away from heat or open flame.
DISPOSAL: Do not reuse empty container. Wrap container and put in trash collection.

EPA REG. NO. 10006-49 • EPA EST. NO. 10006-NJ-1

MANUFACTURED BY:
CONTACT INDUSTRIES, INC.
ELIZABETH, N.J. 07201
MADE IN U.S.A.

Contract WASP & HORNET KILLER II

FOR USE BOTH INDOORS AND OUTDOORS TO KILL HORNETS • YELLOW JACKETS • WASPS • BEES

Dielectric breakdown voltage in accordance with ASTM D 877: No breakdown to 20,000 volts.

SHOOTS A STREAM INTO NESTS, CREVICES, HOLES, ETC. FROM 10 FEET OR MORE AWAY

OCT 28 1987

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 10 806-49

12-88 3550-PR-100 5-15/16 X 8-21/32 1/2-1/8