



ALGAE-SLIME TREATMENT

ACCEPTED

NOV 30 1971

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER-
ED UNDER NO. SUBJECT
TO ATTACHED COMMENTS.

DACARCIDE L-2

USDA REG. NO. 10810-2

Ingredients

Active -

Poly(oxyethylene(dimethyliminio)
ethylene(dimethyliminio)ethylene
dichloride) 15.0%

Inert -

..... 85.0%
Weight per gallon 8.58 lbs.
Weight of active ingredient per gallon 1.29 lbs.

CAUTION: KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish: Do not add treated effluent to lakes, streams or ponds. Use only as directed on label. Destroy empty container.

Applications

DACARCIDE L-2 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water-cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime, and other deposits. An initial slug addition of 4.0 to 9.80 fluid ounces of DACARCIDE L-2 per 1000 gallons of water, to provide a concentration of 32 to 80 parts per million of DACARCIDE L-2 based on the total weight of water in the system, is recommended. Subsequent slug additions of 1.0 to 9.80 fluid ounces of DACARCIDE L-2 per 1000 gallons of water (8 to 80 parts per million of DACARCIDE L-2) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water-cooling towers.

Net Wt: 43 lbs.

DACAR CHEMICAL COMPANY

Carnegie, Pa. 15106