



# ALGAE-SLIME TREATMENT

# DACARCIDE L-5

USDA REG. NO. 10810-2

## Ingredients

### Active -

Poly(oxyethylene(dimethyliminio)ethylene(dimethyliminio)ethylene dichloride) .....	4.0%
------------------------------------------------------------------------------------	------

### Inert -

.....	96.0%
Weight per gallon .....	8.4 lbs.
Weight of active ingredient per gallon .....	.34 lb.

### CAUTION: KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish: Do not add treated effluent to lakes, streams or ponds. Use only as directed on label. Destroy empty container.

## Applications

Dacarcide L-5 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use systems must be cleaned to remove algae growth, microbiological slime and other deposits. An initial slug addition of 15 to 37 fluid ounces of Dacarcide L-5 per 1000 gallons of water, to provide a concentration of 120 to 300 parts per million is recommended.

Subsequent slug additions of 3.7 to 37.0 fluid ounces per 1000 gallons of water (30 to 300 ppm of Dacarcide L-5) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem.

Slug additions should be made in the sump of water-cooling towers.

Net Wt: 42 lbs.

**ACCEPTED**

**NOV 30 1971**

UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND RODENTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
ED UNDER NO. SUBJECT  
TO ATTACHED

## DACAR CHEMICAL COMPANY

Carnegie, Pa. 15106