

BAF-TROL

Active Ingredient

Didecyl dimethyl ammonium chloride..... 18.0%

Inert Ingredient 82.0%

DANGER

KEEP OUT OF REACH OF CHILDREN

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Harmful if swallowed. Avoid contact with skin and eyes. Wear goggles or face shield and rubber gloves when handling. May cause severe eye damage and skin irritation. In case of contact flush immediately with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, DO NOT induce vomiting; drink large amounts of fluids and call a physician. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

EPA REG. NO. 10867-2
EPA EST. NO. 10867-TN-01

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with the label. BAF-TROL is a specially prepared product for controlling algae, bacteria and commercial recirculating water cooling towers, evaporative condensers and its use in air washers, the system should be precleaned, if dirty, by applying a solution to the air washer tank. Let system run 2 hours with fan off. Do not use all nozzles. Remove plugged nozzles and clean manually. Air washers used for tobacco dust or other acidifying materials require periodic adjustment of additives.

COOLING TOWERS & EVAPORATIVE CONDENSERS - Initial Dose: If system is fouled, apply 1 to 1 1/2 quarts of BAF-TROL per 1000 gallons of water in the system until control is achieved. **Subsequent Dose:** When microbial control is evident, add BAF-TROL per 1000 gallons of water in the system every 4 to 7 days or when contaminations of slime or scale must be removed manually.

AIR WASHERS - Initial Dose: When the system is noticeably fouled, apply 1 to 1 1/2 quarts of BAF-TROL per 1000 gallons of water in the system. Repeat until control is achieved. **Subsequent Dose:** When microbial control is evident, add 1/3 to 1 pint of BAF-TROL per 1000 gallons of water in the system, every 3 days or as needed.

Heavy contaminations of slime or scale must be removed manually, BAF-TROL should be used in tower sump, tower basin or on distribution decks.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not stack more than four drums high. Leaking or damaged drums should be removed from service and disposed of in a sanitary landfill. Spills should be absorbed in sand or other absorbent material. Keep container closed when not in use.

PROHIBITIONS: This product is corrosive to mild steel. Do not store in metal containers.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of according to label instructions, contact your State Pesticide or Environmental Hazardous Waste representative at the nearest EPA Regional Office for disposal instructions.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or dispose of in a sanitary landfill or incineration, or if allowed by State and local authorities, by other means approved by the EPA.

GENERAL: Consult Federal, State or Local Disposal authorities for appropriate disposal method.

SOLD BY:

WATER SERVICES, INC.
P.O. BOX 22339
KNOXVILLE, TN 37933-0339

ACC

SEP

Under the Fungicide, Disinfectant and Sanitizer Act of 1972, as amended, registered by EPA Reg. No. 10867-2