

CAUTION: Some fruits and other plants are susceptible to injury from sulphur under certain climatic conditions. The user is advised not to use sulphur on any crop unless local use has proven that sulphur is safe in that locality.

During periods of high temperature sulphur may burn foliage and fruit. Do not make sulphur applications at excessively high temperatures. Do not use LIQUID Sulphur with oil or within 4 weeks of an oil application.

ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DIRECTIONS FOR MIXING Before Using, Stir Until Smooth

Pour recommended amount into partially filled spray tank. Keep agitator running during filling and spraying operations. **DO NOT ALLOW MIXTURE TO STAND.** Failure to maintain agitation will cause LIQUID Sulphur to settle and may necessitate manual stirring to redisperse.

The strong adhesive properties of LIQUID Sulphur act as a sticker on the plant, and the sticking characteristic necessitates the flushing of equipment with

water after each day's use. Sulphur in any form is corrosive material. To reduce the effect, equipment should be flushed daily.

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

RECOMMENDATIONS

Use of this material in a manner other than in accordance with this label may cause serious plant, crop, or personal injury, excessive residues, unsatisfactory control or other unintended consequences.

Unless otherwise specified for specific tree fruits, dosage rates are given as pints of LIQUID Sulphur per 100 gallons water for use in a thorough coverage spray.

APPLE:

Scab:

Pre-bloom through Calyx sprays 1 1/2 to 3 1/2 pints
Cover sprays 1 to 2 pints

Powdery Mildew:

Pre-bloom through Calyx sprays 2 1/2 to 3 pints
Cover sprays 2 pints

PEACH:

Powdery Mildew, Brown Rot, Scab:

Pink and bloom sprays 1 1/2 to 3 1/2 pints
Petal fall, shuck and cover sprays 1 to 1 1/4 pints

CITRUS (Grapefruit, Lemons, Limes, Oranges, Tangelos and Tangerines)

Rust Mite: 1 to 4 pints
Do not apply within 4 weeks of an oil application.

PEANUTS:

Rust: Apply 2 to 4 pints per acre in sufficient water for thorough coverage. Begin application approximately 6 weeks after planting. Repeat at 7 to 10 day intervals as long as rust control is required. Do not apply within 4 weeks of an oil application.

Consult your State Agricultural Experiment Station or State Extension Service Specialist for complete details on the spraying program best suited to your local conditions.

ACCEPTED
8-31-76
10873-48
UNLESS THE FEDERAL INVENTOR
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
ED UNDER NO. 10873-48
TIFTON CHEMICAL COMPANY



TIFTON
TIFCHEM

LIQUID SULPHUR

ACTIVE INGREDIENTS

Sulphur as S 49.4%

INERT INGREDIENTS

50.6%

TOTAL 100.0%

(Contains 6.0 pounds Sulphur per gallon)

KEEP OUT OF REACH OF CHILDREN CAUTION

NOTICE: Seller warrants that the product conforms to its chemical description and is reasonably fit for the purpose stated on the label when used in accordance with directions under normal conditions of use, but neither this warranty nor any other warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use, storage or handling of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to seller, and buyer assumes the risk of any such use. These include, but are not limited to damage to plants, crops and animals to which the material is applied, failure to control pests, damage caused by drift to other plants or crops, and personal injury.

Harmful if swallowed. Avoid breathing spray mist. May cause irritation of nose, throat or skin. Avoid contact with eyes, skin and clothing. Do not contaminate feed and foodstuffs. Do not apply to any area not specified on label. Do not re-use empty container. Wash thoroughly with water and detergent. Puncture, make unuseable. Dispose of in a safe place.

NET CONTENTS 5 GALLONS

EPA EST. NO. 10873-GA-1

EPA REG. NO. 10870-48

Manufactured By

TIFTON CHEMICAL COMPANY

TIFTON, GEORGIA 31794