

aqua-serv engineers, inc.
2431 EAST 56th STREET, LOS ANGELES, CALIFORNIA 90058 • Telephone 582-8246

A-105 MICROBIOCIDES

aqua-serv

EPA REG. NO. 10932-5-AA
EPA EST. NO. 10932-CA-1

FOR THE CONTROL OF ALGAE IN INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

ACTIVE INGREDIENTS

N-Alkyl (60% C14, 30% C16, 5% C12, 5% C18)	
Dimethyl Benzyl Ammonium Chlorides	6.25%
N-Alkyl (50% C12, 30% C14, 17% C16, 3% C18)	
Dimethyl ethylbenzyl ammonium chloride	6.25%
bis (Tributyltin) oxide	2.375%
INERT INGREDIENTS	85.125%

DANGER: KEEP OUT OF REACH OF CHILDREN.

CORROSIVE: Causes eye damage. May produce severe burns. Do not get in eyes, on skin or on clothing. Protect eyes and skin with goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed, inhaled or absorbed through skin. Do not breathe vapor or mist.

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not use in potable water supplies or domestic supplies. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse empty container. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

DIRECTIONS FOR USE: Use only as directed for control of algae in industrial recirculating water cooling towers. Begin treatment at first sign of algae formation or after cleaning systems whose efficiency is already impaired. Badly fouled systems should be cleaned before starting treatment.

INITIAL DOSE: Apply one quart of A-105 per 1000 gallons of water in system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add one quart of A-105 for each 1200 gallons of water in the system weekly or as needed to maintain control. Apply at a point in the system where the product will be uniformly mixed.

WEIGHT: 8 POUNDS PER GALLON

NET WEIGHT:

ACCEPTED

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER
ED UNDER NO. 10932-5