



aqua-serv engineers, inc.

13560 Colombaro Court, Fontana, CA 92335 • (714) 681-9696

10932-18
EPA REG. NO. 10032-18

BEST AVAILABLE COPY

EPA EST. NO. 10032-CA-1

EPA REG. NO. 10032-18

PRECAUTIONARY STATEMENTS

HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams or ponds. Permits may be required for discharge containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

WARRANTY

Manufacturer's guarantee shall be limited to the terms of the label, and subject thereto. The buyer assumes any risk to persons or property arising out of use or handling and accepts the product on these conditions.

NET WEIGHT:

7618

A SPECIALIZED FORMULATION OF ORGANIC SCALE AND CORROSION INHIBITORS CONTAINING A MICROBIOCIDAL FOR USE IN CONTROLLING ALGAE, BACTERIA, AND FUNGI IN COMMERCIAL AND INDUSTRIAL RECIRCULATING WATER COOLING TOWERS AND INDUSTRIAL AIRWASHING SYSTEMS. THIS PRODUCT IS SPECIFICALLY DESIGNED AS A COMPLETE ALL-IN-ONE LIQUID TREATMENT PROGRAM.

ACTIVE INGREDIENTS:

Poly (oxyethylene (dimethyliminio) ethylene-(dimethyliminio) ethylene dichloride) 5%

INERT INGREDIENTS: 95%

This product contains 0.43 lbs. of active ingredient per gallon and weighs 8.71 lbs. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

If Swallowed - Rinse mouth with copious amounts of water then drink promptly a large quantity of water. Do not induce vomiting. Avoid alcohol. Get medical attention.

If In Eyes - Flush with plenty of water for 15 minutes. Get medical attention.

If On Skin - Wash with plenty of soap and water. Get medical attention if irritation persists.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

7618 is used to control scale, corrosion, algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 12 to 30 fluid ounces of 7618 per 1000 gallons of water to provide a concentration of 96 to 240 parts per million of 7618, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 3.0 to 30 fluid ounces of 7618 per 1000 gallons of water (24 to 240 parts per million of 7618) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 12 to 30 fluid ounces of 7618 per 1000 gallons of water used in the system.

SUBSEQUENT DOSE: When microbial control is evident, add 3.0 to 30 fluid ounces of 7618 per 1000 gallons of water used in the system per day.

7618 is used to control scale, corrosion, algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 12 to 30 fluid ounces of 7618 per 1000 gallons of water to provide a concentration of 96 to 240 parts per million of 7618, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

STORAGE

Do not contaminate water, food, or feed. Store in original container. Do not use if container is damaged or leaking.

STORAGE: Do not store in high temperatures. Leaking containers should be placed in overpacks. Containers should be absorbed and disposed of in a safe manner. Do not store in closed when not in use.

PESTICIDE DISPOSAL

Do not use if container is damaged or leaking. Do not use if container is damaged or leaking.

CONTAINER DISPOSAL

PLASTIC: Triple rinse with water for recycling or dispose of in a safe manner, or, if allowed by local authorities, by burning. If burned, do not breathe fumes.

METAL:

Triple rinse with water for recycling or dispose of in a safe manner, or, if allowed by local authorities, by burning. If burned, do not breathe fumes.