

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

WARRANTY

Seller's guarantee shall be limited to the terms of the label, and subject thereto. The buyer assumes any risk to persons or property arising out of use or handling and accepts the product on these conditions.

IN CASE OF EMERGENCY

Endangering life or property involving this product, call CHEMTREC (800) 424-9300

7618

A SPECIALIZED FORMULATION OF ORGANIC SCALE AND CORROSION INHIBITORS CONTAINING A MICROBIOCIDAL FOR USE IN CONTROLLING ALGAE, AND BACTERIA IN COMMERCIAL AND INDUSTRIAL RECIRCULATING WATER COOLING TOWERS AND INDUSTRIAL AIRWASHING SYSTEMS. THIS PRODUCT IS SPECIFICALLY DESIGNED AS A COMPLETE ALL-IN-ONE LIQUID TREATMENT PROGRAM.

ACTIVE INGREDIENTS:

Poly [oxyethylene (dimethyliminio) ethylene-(dimethyliminio) ethylene dichloride] 5%
INERT INGREDIENTS: 95%
TOTAL 100%

This product contains 0.43 lbs. of active ingredient per gallon and weighs 8.71 lbs. per gallon.

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

FIRST AID

If Swallowed:

- Call a poison control center or doctor immediately for treatment advice.
- Have person sip a glass of water if able to swallow.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give anything by mouth to an unconscious person.

If in Eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor immediately for treatment advice.

If on Skin or Clothing

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

Have MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

SEE SIDE PANEL FOR ADDITIONAL
PRECAUTIONARY STATEMENTS

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

7618 is used to control scale, corrosion, algae, and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 12 to 30 fluid ounces of 7618 per 1000 gallons of water to provide a concentration of 96 to 240 parts per million of 7618, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 3.0 to 30 fluid ounces of 7618 per 1000 gallons of water (24 to 240 parts per million of 7618) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 12 to 30 fluid ounces of 7618 per 1000 gallons of water used in the system.

SUBSEQUENT DOSE: When microbial control is evident, add 3.0 to 30 fluid ounces of 7618 per 1000 gallons of water used in the system per day.

ACCEPTED
JUN - 9 2003
Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 10932-18

7618 is used to control scale, corrosion, and bacteria in industrial airwashing systems that maintain effective mist eliminating components. Prior to its use, system should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 44.4 to 74.1 fluid ounces of 7618 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 30.3 to 74.1 fluid ounces of 7618 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL:
PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Net Contents: _____ Lot No. _____

10932-18

6-9-2003