PRECAUTIONARY STATEMENTS

Hazards to humans and domestic animals.

WARNING! May be fatal if swallowed or absorbed through the skin. Harmful if inhaled. May be irritating to the eyes, skin, or respiratory tract. Do not get in eyes, on skin, or on clothing. Use of coveralls and protective clothing, rubber gloves is recommended when brushing or dipping, and use of an approved respirator when aerosolizing. Avoid prolonged and/or repeated breathing of vapors and/or mists. Use only in well ventilated areas. Keep container closed when not in use. Do not take internally.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flush with water for at least 15 minutes. Call a physician. Do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not contaminate water by cleaning of equipment or disposal wastes. Do not apply directly to water.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE. Do not use, pour, spill, or store near heat or open flame. Pilot lights, exhaust and other sparks should not come in contact with vapors. Do not store or use so that they come in contact with useful living plants.

Waterproof oily application cloths after use to avoid spontaneous combustion. Place cloths outside the building away from combustible materials.

STORAGE AND DISPOSAL: Do not use or store in the house. Do not reuse empty container. Crush container and put in trash collection. Keep away from food and feed.

WATCO EXTERIOR WOOD FINISH

WOOD PRESERVATIVE

FOR Easy OIL AND NATURAL FINISHING

Non-Photochemically Reactive-102

ACCEPTED
with COMMENTS
In EPA Letter Dated:

OCT 15 1982

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 11234-4

WATC

ACTIVE INGREDIENTS:
bis(tributyltin) oxide ..... 0.5[illegible]%
[illegible] N-[illegible] ..
[illegible] fungicide ..... 0.5[illegible]%
Inert Ingredients ..... 98.[illegible]%
TOTAL 100.00%

KEEP OUT OF REACH OF CHILDREN
WARNING
HARMFUL OR FATAL IF SWALLOWED
See Side panel [illegible]

NET CONTENTS: [illegible]

BEST DOCUMENT AVAILABLE

11234-4

EXTERIOR WOOD FINISH II
EPA FILE SYMBOL - 11234-U
(T.O.T.O/FOLPET)

O
OR
Ha

SHING OF ALL EXTERIOR WOODS

STEEL FINE WATCO PRODUCTS
FOR WOODS: Finish & Finish · Finish
Exterior Wood Finish · Wood Floor Finish · Redwood Finish · Marine Varnish Finish · Satin Oil · Satin Wax
FOR MASONRY: Concrete Sealer · Tile and Brick Sealer
For a superior finish on all exterior and interior woods.
WATCO "The Original" Penetrating Oil Finishes

WATCO OIL IS 5 IN ONE
1 - SEALS
2 - PRIMES
3 - HARDENS
4 - PROTECTS
5 - FINISHES
IN ONE EASY APPLICATION

Another Quality Product by
WATCO-DENNIS CORPORATION
SANTA MONICA, CALIFORNIA

WATC

such as
Hating Con
Wood Fini
Process for
or wear
Floors up to

in a no

DO n
1. Shi
Sma
2. Flood
Let
3. Res
Surf
fresh
4. WIPE
CLOT

NOTE: O
m

COVERAGE: 100
Do not dup
COLORING: M
UNIVERSAL TINTI
OF WATCO OIL.
TIMES, INTERMI
CONTINUE WELL

THE PR
being beyond
the WATCO-DE
PARTY INTERES
from the use
any kind is in

NO SAFER SINCE 1927

CHILDREN
SUFFOCATED
Read Precautionary St

BEST DOCUMENT AVAILABLE

11234-4

WATCO® EXTERIOR WOOD FINISH

COMBUSTIBLE MIXTURE
DO NOT USE NEAR OPEN FLAME

PRODUCT DESCRIPTION

For use on unfinished unsealed or stained wood surfaces such as siding, doors, windows, fences and all other exterior woodwork. Helps control and prevent against fungal rot and mildew. Watco Exterior Wood Finish is an exclusive super-penetrating oil and resin preserving process for wood - not a surface film or coating which can chip, peel, crack or wear away. Watco soak, primes, stabilizes, preserves, and hardens wood surfaces up to 1½ inches more — all in one easy application.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

APPLICATION DIRECTIONS - SHAKE WELL

Do not apply in wet weather or extreme hot or cold temperatures.

1. Strip any previous finish. Wipe clean and let wood dry. Sand if smooth finish is desired.
2. Flood on heavy saturation of Watco with brush, roller or spray. Let soak in 30 minutes.
3. Resaturate with Watco. Let soak in 15 minutes and then wipe surface completely dry. If surface becomes tacky dissolve with fresh Watco and wipe off.
4. WHEN FINISHED, COMPLETELY IMMERSE ALL APPLICATION CLOTHS IN WATER TO AVOID SPONTANEOUS COMBUSTION.

NOTE: On rough-sawed woods apply Watco with a roller and remove excess with a dry roller.

TECHNICAL DATA

COVERAGE: 200-300 Sq. Ft. per gallon. Do not thin.

COLORING: Add up to 6 ounces of UNIVERSAL TINTING COLORANT PER GALLON OF WATCO OIL. OR FOR SPECIAL COLOR TINTS, INTERMIX WATCO OILS. SHAKE CONTAINER WELL BEFORE APPLICATION.

SURFACE FINISHING: Surface finishes may be applied over aged Watco Finish after 72 hours.

MAINTENANCE: Reapplication of Watco Oil to wood exterior dry will restore the beauty and effectiveness of the finish.

The proper use and application of Watco Products being beyond the control of their exclusive manufacturer, the Watco-Dennis Corporation, and of the Seller, no warranty expressed or implied is made with respect to results from the use of the products. Responsibility for claims of any kind is limited to the purchase price of the material.

BEST DOCUMENT AVAILABLE

11234-4 OCT 15 1982

Exterior Wood Finish II

161 50487
18 1

Watco-Dennis Corporation
1256 22nd Street
Santa Monica, CA 90404

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.

2. Make the labeling changes listed below before you release the product for shipment:

a. Add the phrase "EPA Registration No. 11234-4."

b. On the front panel Ingredients Statement, make sure the words "Active Ingredients" and "Inert Ingredients" are the same type size and aligned to the same margin.

c. Make sure the Child Hazard Warning and the Storage and Disposal headings are in 12 point type.

d. Make sure the Signal Word is in 14 point type.

BEST DOCUMENT AVAILABLE