

PRECAUTIONARY STATEMENTS
 Hazards to humans and domestic animals.
WARNING: May be fatal if swallowed or absorbed. May be irritating to the eyes, skin, or respiratory tract. Do not eat, drink, or use tobacco while using. Do not get on skin or on clothing. Use protective clothing, rubber gloves, and eye protection when brushing, spraying, or using as approved. Wash thoroughly after use. Avoid prolonged and/or repeated breathing of vapors. Do not use in well-ventilated areas. Keep containers closed when not in use. Do not take internally.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flush with water for at least 15 minutes. Call a physician. Do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not contaminate water by cleaning of equipment or disposal. Do not apply directly to water.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE
 Do not use near open flame or heat or other sources of ignition. Do not use in contact with wood, paper, or other materials that may be damaged or used in contact with them. Do not use in contact with useful living plants.

Washwork only application cloths after use to avoid spontaneous combustion. Place cloths in a safe place away from combustibles.

STORAGE AND DISPOSAL: Do not use or store in the home. Do not reuse empty container. Recycle container and put in trash collection. Keep away from food and feed.



For Easy Oil AND NATURAL FINISHING OF

Non-Protocols: ALL ACTIVE-107

ACCEPTED
 with COMMENTS
 in EPA Letter Dated
 OCT 15 1982
 Under the Federal Insecticide,
 Fungicide, and Rodenticide Act
 as amended, for the pesticide
 registered under EPA Reg. No.
 16234-2



WATCO

ACTIVE INGREDIENTS:
 Bis(trichloroethyl) ether... 8.565%
 Inert Ingredients... 91.435%
 TOTAL 100.000%

KEEP OUT OF REACH OF CHILDREN.
WARNING

HARMFUL OR FATAL IF SWALLOWED
 See Side Panel for Additional Information

NET CONTENTS: 128 FL. OZ. 1

11234-5

EXTERIOR WOOD FINISH III EPA FILE SYMCL-11234-L (T.B.T.O.)

OTHER FINE WATCO PRODUCTS

FOR WOODS: Hard Oil Finish - Teak Oil Finish
Exterior Wood Finish - Wood Tone Finish - Redwood Finish - Marine Teakwood Finish - Selen Oil - Selen Wax
FOR MASONRY: Concrete Sealer - Tile and Brick Sealer

For a superior finish on all
essential interior woods.

See WATCO The Original
Brush Oil Finish

WATCO OIL IS 5 IN ONE

- 1- SEALS
- 2- PRIMES
- 3- HARDENS
- 4- PROTECTS
- 5- FINISHES

IN ONE EASY APPLICATION

Another Quality Product by
WATCO-DENNIS CORPORATION
SANTA MONICA, CALIFORNIA

OF ALL EXTERIOR WOODS

FOR YEARS SINCE 1917



STLB

DREN

WARRANTED
100% Satisfaction

WATCO®

DO NOT

For
such as sliding,
Halt Control on
Wood Finish - 1/2 in
Process for 10-15
or 16-18 inches
For 10 to 25

1. Strip and
smooth fi
2. Flood on, let
soak
3. Resistant
surface of
fresh wood
4. WHEN FIN
CLOTHS IN

NOTE: On the
front of

COVERABLE: 200-300

Do not use.
CALIFORNIA: Mix up
UNIVERSAL THINER CO.
OF WATCO OIL OR 5
TENS, INTERMIX WA
CONTAINER WILL BE

The proper
being beyond the
the WATCO-DENNIS
partly expressed or
from the use of the
any kind is limited

11234-5

WATCO® EXTERIOR WOOD FINISH

**COMBUSTIBLE MIXTURE
DO NOT USE NEAR OPEN FLAME**

PRODUCT DESCRIPTION

For use on unfinished and unsealed or stripped wood surfaces such as siding, doors, windows, fences and all other exterior woodwork. Helps control and prevent against fungal rot and mildew. Watco Exterior Wood Finish is an exclusive super-penetrating oil and resin preserving process for wood - not a surface film or coating which can chip, peel, crack or wear away. Watco seals, primes, stabilizes, preserves, and hardens wood surfaces up to 25 percent more - all in one easy application.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

APPLICATION DIRECTIONS-SHAKE WELL

DO NOT apply in wet weather or extreme hot or cold temperatures.

1. Strip any previous finish. Wipe clean and let wood dry. Sand if smooth finish is desired.
2. Flood on heavy saturation of Watco with brush, roller or spray. Let soak in 30 minutes.
3. Resaturate with Watco. Let soak in 15 minutes and then wipe surface completely dry. If surface becomes tacky discontinue fresh Watco and wipe off.
4. WHEN FINISHED, COMPLETELY IMMERSE ALL APPLICATION CLOTHS IN WATER TO AVOID SPONTANEOUS COMBUSTION.

NOTE: On rough-sawn woods apply Watco with a roller and remove excess with a dry roller.

TECHNICAL DATA

COVERAGE: 200-300 sq. ft. per gallon. Do not thin.

COLORING: Mix up to six ounces of UNIVERSAL TINTING COLORANT (see label) OF WATCO OIL. OR FOR SPECIAL COLOR TONES, INTERMIX WATCO OILS. SHAKE CONTAINER WELL BEFORE APPLICATION.

SURFACE FINISHING: Surface finishes may be applied over an unsealed Watco finish after 72 hours.

MAINTENANCE: Application of Watco Oil to wood appearing dry will restore the beauty and effectiveness of the finish.

The proper use and application of Watco Products being beyond the control of their exclusive manufacturer, the Watco-Denais Corporation, and of the seller, no warranty expressed or implied is made with respect to results from the use of the products. Responsibility for claims of any kind is limited to the purchase price of the material.

11234-5

OCT 15 1982

Exterior Wood Finish 111

Matco-Dennis Corporation
1256 22nd Street
Santa Monica, CA 90404

161 80485
18 1

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.

2. Make the labeling changes listed below before you release the product for shipment:

- a. Add the phrase "EPA Registration No. 11234-5."
- b. On the front panel Ingredients Statement, the words "Active Ingredients" and "Inert Ingredients" must be the same type size and aligned to the same margin.
- c. Make sure the Child Hazard Warning and the Storage and Disposal heading are in 12 point type.
- d. Make sure the Signal Word is in 14 point type.

BEST DOCUMENT AVAILABLE

11234-5

-2-

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFM sec. 4(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.


Harry M. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (28-747)

Enclosure

BEST DOCUMENT AVAILABLE