

FORMULA 645 TUNIONE THE FOUNDAL INSECTION FOR FOLIABLE POISON BEGISTED TO BRITE NO. PENETRANT SEALER

COPPER 8--QUINOLINOLATE

Directions For Use PLEASE REFER TO TECHNICAL DATA SHEET CAUTION:

KEEP OUT OF REACH OF CHILDREN. DO NOT USE, POUR, SPILL OR STORE

NEAR HEAT OR OPEN FLAME Do Not Allow Contact With Skin, If Splashed On Skin Wash Thoroughly, With Soap And Water. Do Not Allow Material To Be Splashed In Eyes.

If Splashed In Eyes Wash Eyes Immediately With Copious Amounts Of Water And Secure Immediate Medical Attention.

HARMFUL IF SWALLOWED FOR COMMERCIAL USE ONLY

CONTENTS

EPA REG. NO. 11265-10

5 GALLONG LOS GALETONET:

Do Not Reuse Empty Continuor District It By Perforating Or Crashing Bury Or Discard In A Safe Place, Away Fr. ir. Water Supplies



SEYMOUR CHEMICAL ASSOCIATES INC.

Directions for Use

CAUTION:

NEAR MEAT OR OPEN FLAME

THE SHAPE

HARMIN IF SWALLOWED FOR COMMITTEE ON F

117 411

And the second

Cleaning, Or Lyppianent Or Discovery 1985

1609 ARBOR HIGHLAND PARK, ILL. 60035 SEYMOUR CHEMICAL ASSOCIATES

1609 ARBOR AVENUE

HIGHLAND PARK, ILLINOIS 60035

312/831-9034

Technical Data Sheet

MOLD INHIBITCH

FORMULA 645 PENETRANT SEALER

Containing copper-8-quinolinolate as the active ingredient, FORMULA # 645 PENECHANT SEALER is a ready-to-use waterrepellent preservative formulated to prevent the growth of fungi on interior structural materials inside food processing plants.

FORMULA #645 PENETRANT SEALER can be brushed or sprayed onto WOOD, CONCRETE BLOCK, TILE and masonry used for walls, ceilings, floors and other structural members which support the growth of UNSANITARY mold or mildew.

FORMULA #645 FUNGICIDAL CLEAR is a PENETRANT SEALER. It is formulated to penetrate deep beneath the surface of wood and masonry in order to kill deep-seated infections of fungi and prevent their regrowth.

An antifungal Penetrant Sealer is defined as a surface coating which prevents fungal growth, impregnates the material treated, and leaves no residual film which can be removed by ordinary wear. Consequently, this product cannot peel or flake off like a paint film. As a result, FORMULA #645 has been accepted for the treatment of items such as WOOD RAIL BEAMS, and the ceiling areas above the beams.

A single treatment with FORMULA #645 will keep treated areas mold-free for periods up to several years. Copper-8-quinolinolate will not leach out of wood or concrete under normal plant operating conditions, and it is non-volatile. Treated surfaces can be washed with alkaline cleaners in order to remove dirt or other accumulations without removing the treatment. Due to the excellent mold control, washing can be reduced in a general maintenance program.

FORMULA #645 PENETRANT SEALER is sold in 55 gallon drums as a ready-to-use solution. Coverage will generally exceed 400 square feet per gallon, depending on the porosity of the treated surface.