

WATCO EXTERIOR WOOD FINISH

COMBUSTIBLE MIXTURE

DO NOT USE NEAR OPEN FLAME

PRODUCT DESCRIPTION

For use on unfinished, painted or stained wood surfaces such as siding, doors, window frames, and all other exterior woodwork. Helps control and prevent against fungal rot and mildew. Watco Exterior Wood Finish is an exclusive super-penetrating oil and resin preserving process for wood -- not a surface film or coating which can chip, peel, check or wear away. Watco also penetrates, stabilizes, preserves and hardens wood surfaces up to 25 percent more -- all in one easy application.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

APPLICATION DIRECTIONS

1. Clean wood surface with a brush or wire brush to remove dirt, old finish, and loose wood. Wash with a mild detergent solution and rinse thoroughly. Allow to dry completely.

2. Apply Watco Exterior Wood Finish with a brush, sprayer, or roller. Apply liberally, allowing the product to penetrate the wood. Apply a second coat after 24 hours.

3. For best results, apply Watco Exterior Wood Finish during the warm, dry months of the year.

NOTE: Watco Exterior Wood Finish is not intended for use on metal, masonry, or other non-wood surfaces.

TECHNICAL DATA

COVERAGE: 1 gallon covers approximately 100 square feet of wood surface.

SURFACE FINISHING: Watco Exterior Wood Finish provides a natural, clear finish that enhances the wood's grain and color.

MAINTENANCE: Reapply Watco Exterior Wood Finish every 2-3 years for long-lasting protection.

The proper use and application of Watco Products being beyond the control of their exclusive manufacturer, the Watco-Dennis Corporation, and of the seller, no warranty, expressed or implied, is made with respect to results from the use of the products. Responsibility for claims of any kind is limited to the purchase price of the material.

PRECAUTIONARY STATEMENTS

Hazards to Humans (and Domestic Animals)

DANGER

Corrosive, causes eye and skin damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling.

VITEK 2-DOP should not be used on items which come into contact with food stuffs nor on items of clothing or infant wear.

FIRST AID

If splashed in eyes or on skin wash immediately with copious amounts of water and secure immediate medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

Pesticide Disposal

"Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance."

Container Disposal

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state or local procedures.



VITEK™ 2-DOP

FUNGISTATIC PLASTICIZER-STABILIZER
FOR VINYL COMPOUNDS

ACTIVE INGREDIENT 2.0%
10,10'-Oxybisphenoxarsine
Total Arsenic as elemental As — 0.60%
Water Soluble Arsenic as Elemental As — less than 0.01%
INERT INGREDIENTS 98.0%

KEEP OUT OF REACH OF CHILDREN

— DANGER —

See Left Panel For Additional Precautionary Statements.

FOR INDUSTRIAL USE ONLY

Contents
430 Lbs. Net Wt.

EPA REG. NO. 11245-14
EPA EST. NO. 33765-10-1

Maag, Inc.
Seymour Chemicals
P.O. Box 2408
Tuscaloosa, AL 35403 USA

BEST DOCUMENT AVAILABLE