

WARNING
Keep out of
reach of children
(other warnings
on back panel)



HELM'SMAN

Active Ingredients Percent
Bisphenol A 10
Epoxy Resin 90
Inert Ingredients 100

ACCEPTED
2-8-72

Graphspeed
POLYURETHANE-GRAPHITE
ANTI-FOULING
Racing Bottom Finish
Fresh Water

1 QUART U.S.

11266-3

INSTRUCTIONS FOR USE
1. SURFACE PREPARATION
Remove all old paint, dirt, grease, and debris from the hull. Sand the hull with fine sandpaper (60-80 grit) to a smooth finish. Wash with clean water and allow to dry completely.
2. APPLICATION
Apply Graphspeed to the hull with a brush or spray gun. Apply a thin, even coat. Allow to dry for 24 hours. A second coat may be applied if desired.
3. PRIMER
For glass hulls, use a suitable epoxy primer. For wood hulls, use a suitable wood primer.
DO NOT APPLY TO METAL HULLS

WARNING:
CONTAINS Bisphenol A, Epoxy Resin
HARMFUL May be harmful if inhaled or absorbed.
CAUSES Irritation to the skin and eyes.
AVOID Contact with skin and eyes.
FLAMMABLE Do not use near open flame or heat.
Helm'sman U.S.A., Inc.
New York, N.Y.
Manufactured by
A. E. Helmsman, Inc., New York, N.Y.
© 1972