

FRONT LABEL

WOODSMAN[®]

ACCEPTED

APR 28 1988

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended by the FIFRA Act
of 1972, 1974, and 1978



SEMI-TRANSPARENT OIL STAIN AND WOOD PRESERVATIVE

- Water Repellent
- Resists Mildew
Rot & Decay

Our Best
TRU:TEST

Supreme

MILDEW
RESISTANT—
TREATED WITH
FUNGICIDE TO PROTECT
THE PAINT ITSELF FROM
THE GROWTH OF MILDEW

KEEP OUT OF REACH
OF CHILDREN

WARNING!
COMBUSTIBLE

Contains Petroleum Distillates
[See other precautions on back panel]

ACTIVE INGREDIENT:
3-Iodo-2-Propynyl
Butyl Carbamate 0.5
INERT INGREDIENTS: ... 99.5
100.0

EPA REG. NO. 11263 -
EPA EST. NO. 12140-11-3

- for siding, shingles, decks • water repellent
- resists mildew, rot and decay

IF INHALED: Remove victim to fresh air and administer artificial respiration as needed.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not apply directly to any body of water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS: COMBUSTIBLE. Do not use, pour or spill near heat or open flame. In case of fire, use water, spray, foam, carbon dioxide or dry chemical.

FINISH	SEMI-TRANSPARENT
AVERAGE COVERAGE	100-200 Sq.Ft. - 1st Coat 100-300 Sq.Ft. - 2nd Coat
DRY TIME	Allow 12-15 hours between coats. Thorough drying requires 24 hrs.
THINNER	None required
APPLICATION	Brush, Roller or Spray
PRIMER	None required
CLEAN UP	Paint Thinner.

Sold Exclusively by



Hardware Stores & Home Centers

GENERAL PAINT & CHEMICAL CO. DIVISION OF COTTER & COMPANY
100% MEMBER OWNED CHICAGO, ILLINOIS 60614

True-Test Supreme our Very Best Quality

WOOD PRESERVATIVE

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is for exterior use only and is recommended for shingles (not asbestos), shakes, clapboards, smooth or rough-cut wood siding, decks, porches, railings, outdoor furniture, structural support timbers, flat beds, cold frames and greenhouses. Surfaces that may be in continuous contact with skin should be coated with a varnish or lacquer after treatment. The product is not recommended for use on primed or previously painted surfaces nor for wood used for ground, food, feed, or potable water contact. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood.

WOODSMAN SEMI-TRANSPARENT OIL STAIN & WOOD PRESERVATIVE is modified to give water repellancy, resist rot, decay and mildew. It may be applied to previously stained surfaces of similar or lighter color. One coat gives full protection, two coats deepen and intensify the color. On very porous or badly weathered wood, a second coat is recommended.

FOR DECKS: Apply only one coat, well brushed to improve penetration and adhesion.

Semi-Transparent Stain coats the surface of the wood as well as penetrates but still allows the wood grain and texture to show. If repainting is ever desired, surface must be well weathered.

APPLICATION:

Surface must be clean, free of dirt, grease and mildew (consult dealer for removing mildew). Mix well before using and stir often during the application. Always buy enough stain for the complete job; when applying inter-mix all containers of the same color to assure color uniformity.

Apply liberally. Cover a small area at a time and keep a wet edge to avoid lap marks. Work in the direction of the siding. Do not stop in the middle of an area; try to work to edges or corners. Avoid direct sunlight when applying; follow shaded side around house, if possible. Do not apply before dew has evaporated or immediately before (or after) a rain. Since different woods "take" stains differently, test first on similar type of wood to which stain is to be applied. Treated wood must be allowed to weather a minimum of one to two years before applying any stain.

STORAGE AND DISPOSAL

STORAGE. Do not expose this product to excessive heat.

DISPOSAL: Securely wrap original container in several layers of newspaper and discard in trash. Do not reuse container.