

11283-12 159070 1005

<b>U.S. ENVIRONMENTAL PROTECTION AGENCY</b> <b>OFFICE OF PESTICIDES PROGRAMS</b> <b>REGISTRATION DIVISION (TS-757)</b> <b>WASHINGTON, DC 20460</b>	<b>EPA REGISTRATION NO.</b> 11283-12	<b>DATE OF ISSUANCE</b> JAN 27 1986
	<b>TERM OF ISSUANCE</b> Conditional	
	<b>NAME OF PESTICIDE PRODUCT</b> WOODMAN SOLID COLOR Oil Stain and Wood Preservative, Neutral base, 351-1	

**NOTICE OF PESTICIDE:** ☒ REGISTRATION  
☐ REREGISTRATION  
(Under the Federal Insecticide, Fungicide,  
and Rodenticide Act, as amended)

**NAME AND ADDRESS OF REGISTRANT (Include ZIP code)**

General Paint & Chemical Company  
201 Jenkins Road  
Carv, IL 60013

16/ 159070  
18/ 1

**NOTE:** Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others. This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:


1. Submit one or cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment:
  - a. Add the phrase "EPA Registration No. 11283-12."
  - b. As stated in our September 9, 1985 letter the statement, "No sealers are necessary for frequent dermal contact surfaces" must be deleted. The Agency is currently reviewing a submission proposing deletion of statement. As of today, the Agency has not made a decision on this proposal.
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

☐ ATTACHMENT IS APPLICABLE

**SIGNATURE OF APPROVING OFFICIAL** *Lucy M. Xacoby* **DATE** 1/27/86

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

  
Henry M. Jacoby  
Product Manager (21)  
Fungicide-Herbicide Branch  
Registration Division (TS-767C)

Enclosures

FRONT LABEL

# WOODSMAN

exterior/solid color oil

## Stain and Wood Preservative

A LIMITED WARRANTY TO CONSUMERS  
★  
• Good Housekeeping •  
PROMISES  
REPLACEMENT OR REFUND IF DEFECTIVE

MILDEW  
RESISTANT —  
TREATED WITH  
FUNGICIDE TO PROTECT  
PAINT ITSELF FROM  
GROWTH OF MILDEW

KEEP OUT OF REACH  
OF CHILDREN

**WARNING!**  
COMBUSTIBLE

Contains Petroleum Distillates  
See other precautions on back panel

ACTIVE INGREDIENT:  
3-Iodo-2-Propynyl  
Butyl Carbamate . . . . 0.5%  
INERT INGREDIENTS: . . . 99.5%  
100.0%

EPA REG. NO. 11263 -  
EPA EST. NO. 12140-11.-3

Our Best  
**TRU-TI**  
Stain

• for siding, shutters, decks  
• resists mildew, rot, and

medical attention. IF ON SKIN: Wash with plenty of soap and water.  
IF INHALED: Remove victim to fresh air and administer artificial respiration as needed.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not apply directly to any body of water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS: COMBUSTIBLE. Do not use, pour or spill near heat or open flame. In case of fire, use water, spray, foam, carbon dioxide or dry chemical.

FINISH	SEMI-TRANSPARENT
AVERAGE COVERAGE	100-200 Sq.Ft. - 1st Coat 100-300 Sq.Ft. - 2nd Coat
DRY TIME	Allow 12-15 hours between coats. Thorough drying requires 24 hrs.
THINNER	None required
APPLICATION	Brush, Roller or Spray
PRIMER	None required
CLEAN UP	Paint Thinner.

Sold Exclusively by



Hardware Stores & Home Centers

GENERAL PAINT & CHEMICAL CO. DIVISION OF COTTER & COMPANY  
100% MEMBER OWNED CHICAGO, ILLINOIS 60614

*True-Test Supreme our Very Best Quality*

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is for exterior use only and is recommended for shingles (not asbestos), shakes, clapboards, smooth or rough-cut wood siding, decks, porches, railings, outdoor furniture, structural support timbers, flat beds, cold frames and greenhouses. No sealers are necessary for frequent dermal contact surfaces. The product is not recommended for use on primed or previously painted surfaces nor for wood used for ground, food, feed or potable water contact. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood.

WOODSMAN SOLID COLOR OIL STAIN & WOOD PRESERVATIVE is modified to give water repellantcy, resist rot, decay and mildew. It may be applied to previously stained surfaces of similar or lighter color. One coat gives full protection, two coats deepen and intensify the color. On very porous or badly weathered wood, a second coat is recommended.

1. DECKS: Apply only one coat, well brushed to improve penetration and adhesion.

Solid Color Stain coats the surface of the wood as well as penetrates but still allows the wood grain and texture to show. If repainting is ever desired, surface must be well weathered.

#### APPLICATION:

Surface must be clean, free of dirt, grease and mildew (consult dealer for removing mildew). Mix well before using and stir often during the application. Always buy enough stain for the complete job; when applying inter-mix all containers of the same color to assure color uniformity.

Apply liberally. Cover a small area at a time and keep a wet edge to avoid lap marks. Work in the direction of the siding. Do not stop in the middle of an area; try to work to edges or corners. Avoid direct sunlight when applying; follow shaded side around house, if possible. Do not apply before dew has evaporated or immediately before (or after) a rain. Since different woods "take" stains differently, test first on similar type of wood to which stain is to be applied. Treated wood must be allowed to weather a minimum of one to two years before applying any stain.

#### STORAGE AND DISPOSAL

**STORAGE.** Do not expose this product to excessive heat.

**DISPOSAL:** Securely wrap original container in several layers of newspaper and discard in trash. Do not reuse container.