



ATIVE

)ANGER — FLAMMABLE

UL OR FATAL IF SWALLOWED itional Precaution On Back Panel **)UT OF REACH OF CHILDREN**

ALLON (128 FI. Oz.)

DIRECTIONS

For best results the wood should be completely immersed as PROLONG PENTA comes from the container. For maximum protection immerse 5 minutes per inch of thickness. Important for joints, end of grain, exposed wood and where in contact with ground or masonry.

For protection against termites treat wood prior to use in construction.

Fence posts, poles, foundation timbers and heavy wooden members should be free of bark, dry and wellseasoned and immersed in the product for a period of 12 to 48 hours to be an effective wood preserver.

Lumber intended to be in contact with the soil should be dipped for a minimum of 3 minutes or if treated by brush or spray method, receive two or more flowing coats.

Where immersion is not possible or practical, a heavy brush application may be applied. Framing should be completed and wood should be dry before application. Cut and remove unsound wood two feet beyond decay. Allow at least one hour between coats and do not paint until dry (approximately 24 hours). One gallon will treat 250 to 400 sq. ft. of lumber.

PROLONG PENTA kills rot-producing fungi and molds and thus stops rot and decay. PROLONG PENTA treated wood will pick up only a minimum amount of moisture thus warping, shrinkage, and swelling is reduced. Treat windows, doors and frames for easy operation.

PROLONG PENTA kills and prevents re-infestation of wood-destroying insects such as termites, powder-post beetles, carpenter ants, etc.

Do not reuse empty drum or container. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish and wildlife. Do not contaminate water by cleaning of equipment or disposal of wastes.

Notice: Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

Federal Spec. TT-W-572

DANGER – FLAMMABLE – TOXIC

Harmful or fatal if swallowed. Contains petroleum distillate. Do not induce vomiting. Avoid breathing of vapors. Do not pour, spill, or store near heat or open flame. Close after use. Use with adequate ventilation. Do not get in eyes, on skin or on clothing. Wear rubber gloves and protective clothing when handling the freshly treated lumber. May be fatal if absorbed through skin.

KEEP OUT OF REACH OF CHILDREN

