

NET ONE GALLON



5-17-76

UNDER THE FEDERAL INSLOTICIDE EVEL DE PODENTICIDE ACT EVEL DE MIC POLON REGISTERED UNIT : PD. 11292 3

ACCEPTED 5-17-76 UNDER THE FEDERAL INSUSTICIDE FUNCICIDE / 10 RI DENTICIDE ACT FOR ECUNIOMIC FOICON REGISTERED UNDER THD. 112923

ANU ... WITH RUST INHIBITORS WE RUST TO CLEAN AND DISINFECT TOILET BOWLS REMOVE W/ DISPENSER UPSIDE DOWN V UNDER RIM OF BOWL TWO PENSER, MOVING COMPLE CONTACT WITH SURFACE U SIDES ALLOW 2 OUNCES MI SWAB ENTIRE AREA OF BOV SEAT AND COVER WIPE WI URINALS: PLACE CLEAN MO CLEAN URINAL THOROUGH INTO GROVES, ALONG SIDE FACE IS CLEAN, REMOVE OUNCES CLEANER AROUN

SCREEN FLUSH WELL

∽-

MADE FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY CONTENT, 1 GAL. PRODUCT OF U.S.A. KEEP CONTAINER CLOSED WHEN NOT IN USE. FIRST AID: IF SWALLOWED CALL A PHYSICIAN IMMEDIATELY. DRINK A TEASPOON OR MORE OF MILK OF MAGNESIA OR A CUP OF SOAPY WATER FOLLOWED WITH MILK OR RAW EGG WHITE.

EYE CONTACT WASH WITH WATER FOR 15 MINUTES GET PROMPT MEDICAL ATTEN. TION

SKIN CONTACT WIPE OFF THE ACID GENTLY IMMEDIATELY FLOOD THE SURFACE WITH WATER USING SOAP FREEL: THEN COVER WITH MOIST MAGNESIA OR BAKING SODA

NOTE EMPTY CONTAINER AND RINSE WITH WATER BEFORE DISPOSING IN CASE OF SPILLAGE WASH AREA WITH WATER AVOID SPLASHING ON NYLON AND COTTON KEEP CONTAINER CLOSED WHEN NOT IN USE

MANUFACTURED BY CHEMIFAX LA MIRADA, CA

WITH RUST INHIBITORS WEITING AGENTS AND EMPLSIF EREST OF A SECONDAN'

TOILET BOWLS REMOVE WATER FROM BOWL BY FORCING WATER OVER TRAP. HOLD DISPENSER UPSIDE DOWN WITH OPENING WATER CONTROL CAP POINTED DIRECTLY UNDER RIM OF BOWL TWO INCHES FROM SURFACE. AND SLIGHT PRESSURE ON DIS PENSER. MOVING COMPLETELY AROUND BOWL, ALLOWING STREAM TO COME IN CONTACT WITH SURFACE UNDER RIM. CLEANE -: WILL THEN FLOW DOWN AND WET SIDES ALLOW 2 OUNCES MINIMUM TO ENTER BOWL. ALLOW TO REMAIN 10 MINUTES SWAB ENTIRE AREA OF BOWL WITH MOP. SWAB SEAT AND COVER AFTER CLEANING SEAT AND COVER WIPE WITH WET SPONGE. FLUSH TOILET.

URINALS: PLACE CLEAN MOP OVER TRAP IN URINAL AND SATURATE WITH CLEANER CLEAN URINAL THOROUGHLY, BE SURE TO WET ENTIRE SURFACE. WORK CLEANER INTO GROVES, ALONG SIDE, AT WATER OUTLET AND AT TOP OF URINAL AFTER SUR-FACE IS CLEAN, REMOVE SCREEN AT URINAL TRAP AND POUR MINIMUM OF 2 OUNCES CLEANER AROUND DRAIN OPENING AND INTO DRAIN OUTLET. ALLOW CLEANER TO WORK 10 MINUTES THEN SWAB INSIDE OF PIPE THOROUGHLY. REPLACE