



5806

VIN-CLAD

VINYL ANTI-FOULING
RED

KEEP OUT OF REACH OF CHILDREN

ACCEPTED
JUL 14 1975
United States Federal Government
Department of the Interior
Bureau of Reclamation
Alaska Division
A.D. No. 1134

EPA EST. No. 44-51-A

FOR INDUSTRIAL USE ONLY

DIRECTIONS

SURFACE PREPARATION: Surface must be clean. All dirt, grease, oil, etc. must be removed by grit blasting or wire brushing. If necessary, use a solvent to remove old peeling paint.

MIXING: Mix paint thoroughly before using. The color may change slightly after several days of storage. The paint is not to be mixed with any other paint or solvent.

APPLICATION: Brush or Roller: Apply to surface with brush or roller. Do not apply to wet surfaces. Allow to dry before reapplying.

Spray: Apply to surface with spray gun.

Air: Do not breathe spray. Avoid contact with eyes, nose, mouth, and skin. If contact occurs, wash immediately with plenty of water.

Airless: Do not breathe spray. Avoid contact with eyes, nose, mouth, and skin. If contact occurs, wash immediately with plenty of water.

CAUTION - COMBUSTIBLE: Do not use near fire, sparks, or open flame. Keep away from heat. Harmful if swallowed. May be absorbed through skin. Causes skin irritation. Avoid breathing spray mist. Do not get eyes, nose, mouth, or skin wet.

If eye contact occurs, immediately wash with plenty of water. If irritation persists, get medical attention. Wash contaminated clothing before reuse. Avoid storage near food and food products. Because the ingredients of this paint may cause allergic reactions to some sensitive skin, avoid prolonged contact with wet or dry paint.

DO NOT reuse container. Destroy when empty. DO NOT contaminate water by cleaning or pouring out contents.

1 GALLON

STANDARD PAINT & VARNISH CO.
NEW ORLEANS, U.S.A.