



**SIGMA  
COATINGS, INC.**

**MARINE AND INDUSTRIAL COATINGS**

**SIGMAPLANE  
ANTI-FOULING  
RED BROWN**

**7287**

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

**SEE BACK PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS**

**ACCEPTED**  
OCT 30 1981  
Federal Insecticide  
and Rodenticide Act  
EPA Reg. No. 41324-23

NOTICE TO THE USER  
OF THIS PRODUCT  
READ THE INSTRUCTIONS  
ON THE BACK PANEL  
OF THE PRODUCT  
FOR THE MOST  
EFFECTIVE USE  
AND SAFETY  
INSTRUCTIONS  
SEE THE BACK PANEL  
FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS

**WORLD WIDE LEADERS IN COATINGS**

**PRECAUTIONARY STATEMENTS  
HAZARD TO HUMANS &  
DOMESTIC ANIMALS  
DANGER**

Corrosive. Causes burns. Do not get on skin. Causes severe eye irritation and rubber gloves. Causes eye irritation. Avoid contact with eyes. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapors. When product is used in confined areas, it should be sprayed, wear protective clothing and a self-contained respirator, only approved by the Mine Safety and Health Administration, formerly the U.S. Bureau of Mines, and by the National Institute for Occupational Safety and Health, or the product must be used with a respirator if swallowed.

**FIRST AID**

**If in eyes:** Flush with plenty of water, get medical attention if irritation persists.  
**If on skin:** Wash with plenty of soap and water, get medical attention if irritation persists.  
**If swallowed:** Drink plenty of water, get medical attention if irritation persists. Do not induce vomiting. If these symptoms persist, get medical attention. **Note to physicians:** This product is a corrosive agent. Do not treat the use of gastric lavage.  
**If inhaled:** Remove to fresh air.

**ENVIRONMENTAL HAZARD**

Do not contaminate water, food, or feed by storage or disposal.

**PHYSICAL OR CHEMICAL HAZARD**

Flammable liquid, N.F.P.A. 2-2-1  
Corrosive, N.F.P.A. 2-1-1

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**SURFACE TO BE COATED:** Surface must be sound, clean and dry. Remove rust and millscale by grit blasting or wire brushing. Gritsweeping is best to remove old peeling paint. Antifouling should be applied over Sigma recommended anticorrosive coating.

**MIXING:** Mix paint thoroughly by stirring from bottom up. Then pour from one container to another several times till paint is uniform. The paint is supplied in ready-to-use consistency. If thinning is necessary, use sparingly. Maximum 10%.

**APPLICATION: Airless:** Adjust pump to obtain proper atomization. If thinning is necessary, use sparingly.

**Air Spray:** Stir material thoroughly and put into pressure pot. Adjust pot pressure and gun pressure so that adequate atomization is obtained.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal.

**PESTICIDE DISPOSAL:** Pesticide spray mixture or residue that cannot be used according to label instructions must be disposed of according to Federal, State, or local procedures under the Resources Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.



**SIGMA COATINGS, INC.**  
3300 RIVER ROAD  
HARVEY, LA 70058