

PRECAUTIONARY STATEMENTS
HAZARDOUS TO HUMANS & DOMESTIC ANIMALS

WARNING

Contains Petroleum Distillate Solvents

HAZARDS TO HUMANS

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe dust, vapor or spray mist. While spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Drink promptly a large quantity of milk, egg whites, gastric solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
 If in eyes: Flush with plenty of soap and water. Get medical attention.
 If on skin: Wash with plenty of soap and water. Get medical attention.
 If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS: Do not contaminate water by cleaning of equipment or disposal of wastes. This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved facility.

PHYSICAL OR CHEMICAL HAZARDS - FLAMMABLE: Keep away from heat and open flame.

MAY BE USED IN SALT OR FRESH WATER

IMPORTANT: DO NOT REUSE CONTAINER WHEN EMPTY. WRAP AND PUT IN TRASH COLLECTION.

NOTES: When product is used in confined areas or applied by a sprayer, wear a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly U.S. Bureau of Mines) and the National Institute for Occupational Safety and Health under the provisions of 29 CFR 11.



Ship Cote®



130 ANTI-FOULING COPPER BOTTOM RED

KEEP OUT OF REACH OF CHILDREN.

WARNING!
 VAPOR HARMFUL CAUSES EYES IRRITATION

See also label for additional precautionary statements.

NET CONTENTS: 1 GALLON (3.786 Liters)

ELLIS PAINT COMPANY
 Long Beach, California 90813

EPA REG. No. 11392-5
 EPA EST. NO. 11392C401

ACTIVE INGREDIENTS	41%
Carrier Solvent	58%
NET INGREDIENTS	99%
TOTAL	100%
Copper expressed as metallic	37.19%

ACCEPTED
 JUN 14 1982
 U.S. Environmental Protection Agency
 Federal Insecticide, Fungicide, and Rodenticide Act
 EPL 11392-5

130 ANTI-FOULING COPPER BOTTOM RED

Ship Cote 130 Red Anti-Fouling is a lead base A/F paint engineered to protect underwater surfaces against marine fouling organisms such as barnacles, hydroids, organic growth and algae. It contains a very high copper content for being a so-called "soft" type. A/F bottom paint #130 contains a plasticizer that protects against cracking and flaking.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its label.

PREPARATION OF SURFACE:

Steel Hulls: Be sure vessel is dry, clean and free of all grease and other foreign substances.

Old Bottom Paint: Remove all fouling, growth, dirt, grease and loose paint. Wash down (briskly rub) with sand or coarse sandpaper. Fiberglass Hulls: Thoroughly clean with clean rags and the Syn-Lex Reducer (or wax and grease remover) to remove wax, oil, grease or any other foreign matter. Wet sand with 220 grit wet or dry sandpaper and rinse with fresh water. Abrate surface 1/4" x 1/4" x 1/4" square.

Welds: Scuffblast to clean metal and apply no less than three coats of Anti-Fouling Primer (Epoxy) 86-75 Solvent Zinc Chromate. Total dry film thickness must be 8 mils.

APPLICATION:

Apply five or more coats at package consistency 4-6 hours apart. Best results are obtained from 6-48 hours after final coat is applied. A/F bottom paint can be made with brush, roller or airless spray.

THINNING:

Thin only if paint thickens up one hour from spraying with Ellis Paint Thinner.

NOTE: Be sure paint is thoroughly stirred both before and during application.

Use only with adequate ventilation. Do not take internally. KEEP OUT OF REACH OF CHILDREN. See Precautionary Statements.