

When **HYDRATONE** is used as directed, it will aid in controlling and/or preventing the development of unsanitary slime conditions which are unsightly, produce foul odors and which are often the cause of equipment breakdown.

HYDRATONE is compatible with virtually all corrosion inhibition additives, but should not be used in the presence of soap or other anionic detergents. At use dilution it is non-corrosive to inanimate surfaces.

DANGER

KEEP OUT OF REACH OF CHILDREN. Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN:

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams or ponds.

HYDRATONE

CONCENTRATED SLIMICIDE

and ALGAECIDE

FOR
AIR CONDITIONING
AND
COMMERCIAL RE-CIRCULATING
WATER COOLING TOWERS

Helps Keep Water Systems Clear
Free of Visible Algae Slimes
Inhibits the Growth of Bacteria

Active Ingredients:

n-Alkyl (60% C ₁₄ ; 30% C ₁₆ ; 5% C ₁₂ ; 5% C ₁₈)	
dimethyl benzyl ammonium chlorides	5%
n-Alkyl (68% C ₁₂ ; 32% C ₁₄) dimethyl ethylbenzyl ammonium chlorides	5%
Inert Ingredients	90%

DANGER:
KEEP OUT OF REACH OF CHILDREN.
SEE OTHER WARNINGS ON SIDE PANEL.

Sold By
CONTROL CHEMICAL CORPORATION
2090 ROUTE 110
FARMINGDALE, N.Y. 11735

Code # 82-01800

U.S.D.A. Reg. No. 11524-2

Net Contents:

DIRECTIONS FOR USE

INITIAL DOSE: 1-2 gallons **HYDRATONE** to each 5,000 gallons of water contained in the system.

PERIODIC DOSE: 1-3 quarts **HYDRATONE** to each 5,000 gallons of water contained in the system every 7 days or sooner should visible growth appear.

Pour required amount of **HYDRATONE** (1) directly into water tower or sump, or (2) add through a by-pass valve or injection pump.

For best results, clean heavily contaminated systems before treatment with this product. If soap or anionic detergent is used, rinse thoroughly before charging with **HYDRATONE**.

Do not be alarmed with the sudden appearance of organic debris in the system during the first week of operation. This is normal and is a good indication that **HYDRATONE** has effectively penetrated and dislodged dead organic material which tenaciously adheres to metal and wooden surfaces as living matter. This debris should be removed from the system to avoid clogging of screens and pipes.

Rinse empty container thoroughly with water and discard it.