

BAF - 6

COMPOSITION

	Percent By Weight
Active Ingredient	1.20 percent
Poly[oxyethylene(dimethylamino)ethylene(dimethylamino)ethylene dichloride]	
Inert Ingredient	98.80 percent
Weight Per Gallon	8.32 pounds
Weight of Active Ingredient Per Gallon	0.1 pound

APPLICATION

BAF-6 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 2 to 5 quarts of BAF-6 per 1000 gallons of water, to provide a concentration of 501 to 1260 parts per million of BAF-6 based on the total weight of water in the system is recommended. Subsequent slug additions of 0.5 to 5 quarts of BAF-6 per 1000 gallons of water (126 to 1260 parts per million of BAF-6) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

EPA Reg. No. 11529-3

Manufactured By
FARRIS CHEMICAL CO., INC.
7213 KINGSTON PIKE
KNOXVILLE, TENNESSEE 37919