BAR-N 40

[illegible]

[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]

APPLICATIONS

BAR-N 40 is used to inhibit the growth of algae, bacteria and fungi in recirculating commercial and industrial cooling water systems. Before treatment with BAR-N 40, systems must be cleaned to remove rust, dirt, [illegible] microbiological slime, and other [illegible]. Then the system should be treated with an initial application of 5.1 to 10.2 fluid ounces of BAR-N 40 per 1,000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 1.7 to 10.2 fluid ounces of BAR-N 40 per 1,000 gallons of water should be made every 1 to 5 days or as needed. The required frequency of treatment depends on the relative amount of bleedoff and the severity of the microbiological problem. Slug additions of BAR-N 40 should be made to the sump of water cooling towers.

WARNING

[illegible]

Contact with [illegible] causes irritation. [illegible] skin, or on clothing [illegible] Avoid contamination of food.

FIRST AID: In case of contact, immediately flush [illegible] skin with plenty of water for at least 15 minutes. For eyes, [illegible] flush [illegible] and clothing [illegible].

[illegible] of product [illegible] can safely dry off [illegible] water [illegible] washing with soap or [illegible] water [illegible].

[illegible] contaminated [illegible] destroy by performing [illegible].

[illegible] should be discharged where [illegible]

[illegible]