Micro Bio Cor	trol_W-30	l
Micro Bio Cor	ACCEPTED	
•	APR 1 4 1981 Under the Federal Insecticida, Funglide, and Rotanticide Act. In a particide for the particide	
ACTIVE INGREDIENT: Poly(oxyethylene (dimethyliminio) ethylen (dimethyliminio) ethylene dichloride)	EPA Reg. No.	F ).0
INERT INGREDIENT		).0
This product contains 2.67 lb. of active ingre	edient per gallon and weighs 8.	9

# **KEEP OUT OF REACH OF CHILDREN**

per gallon.

J

# CAUTION

### **PRECAUTIONARY STATEMENTS**

#### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites. gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS. This pesificide is tokin to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Augusty.

# DIRECTIONS FOR USE **GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Micro Bio Control W-30 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of Micro Bio Control W-30 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of Micro Bio Control W-30, based on the total weight of water in the system, is recommended. Repeat initial dosage until control is avident.

Subsequent slug additions of 0.47 to 4.75 fluid ounces of Micro Bio Control W-30 per 1000 gallons of water (4 to 40 parts per million of Micro Bio Contiol W-30) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

Micro Bio Control W-30 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 7.1 to 11.9 fluid ounces of Micro Bio Control W-30 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 4.8 to 11.9 fluid ounces of Micro Bio Control W-30 per 1000 gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or to the water collection trays of the airwash system.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

- TH METAL CONTAINERS: Triple II PLASTIC CONTAINERS: Do not rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.
  - reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Manufactured by: Farris Chemical Co., Inc. P.O. Box 22339, 856 Lovell Rd., Knoxville, TN 37922 EPA REG. NO 11529-11 EPA EST. NO. 11529-TN-01

NET CONTENTS

4 <sup>1</sup>

•

· . · •