O'B-ALGE-670

COMPOSITION

Percent by Weight

Active Ingredient 10.0%
Poly oxyethylene (dimethyliminio) ethylene (dimethyliminio)—ethylene dichloride 10.0%
Inert Ingredient 90.0%
Weight per gallon 8.49 pounds
Weight per gallon of active ingredient per gal 0.85 pound

-APPLICATION-

O'B Alge 670 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of O'B Alge 670 per 1,000 gallons of water to provide a concentration of 48 to 120 parts per million of O'B Alge 670 based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.53 to 15.32 fluid ounces of O'B Alge 670 per 1,000 gallons of water (12 to 120 parts per million of O'B Alge 670) should be employed every 2 to 5 days as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions sappled by PTED made in the sump of water cooling towers.

CAUTION — Keep Out of Reach of Children

UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND RODENTICIDE ACT FOR ECONOMIC POISON REGISTER.

Harmful if swallowed. Do not get in eyes. Avoid skin contact. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not discharge treated effluent where it will drain into lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

Manufactured By:

O'Brien Industries, Inc.

EPA Reg. No. 11541-7

513 W. Mount Pleasant Avenue Livingston, New Jersey 07039