

**SHARE**  
CORP.

# ALGAECIDE

CONTROLS ALGAE GROWTH IN SWIMMING P

Non-inflammable and non-volatile  
in recommended use dilutions.

ACTIVE INGREDIENTS

1,1,1-Trichloro-2,2,2-trifluoroethane  
1,1,1-Trichloro-2,2,2-trifluoroethane  
1,1,1-Trichloro-2,2,2-trifluoroethane

INERT INGREDIENTS

DANGER

KEEP OUT OF REACH OF CHILDREN

Preventive Statement: On the Panel

137

pesticide

11047-36

**SHARE CORP.**  
BROOKFIELD, WIS. 53005  
Chemical Engineering Specialists

Products formulated for professional application, specifically for municipal, industrial and institutional use.

# ALGAECIDE

# IMPERIAL VITRON A.F. BASE

ACCEPTED

September 4, 1977

11553-1

**WARNING!**  
**KEEP OUT OF REACH OF CHILDREN!**

#### PROFESSIONAL USE ONLY

Net Wt. 6.6 lbs./gallon  
Net 2.5 gallons  
E.P.A. Reg. No. 11553-1

Active Ingredients  
Tributyltin acetate 9.21%  
Tributyltin fluoride 1.04%

Inert Ingredients 89.75%  
Calcium carbonate  
Coal Tar Pitch  
Triethylene amine bis (ketimene)  
Silica

Manufactured by

**SOUTHERN IMPERIAL COATINGS CORPORATION**  
NEW ORLEANS, LA. 70129 U.S.A.

**WARNING! KEEP OUT OF REACH OF CHILDREN**  
**MAY CAUSE SEVERE EYE BURNS**  
**MAY BE FATAL IF SWALLOWED**  
**MAY CAUSE SKIN IRRITATION**

**USE CHEMICAL MASK AND EYE PROTECTION! AVOID SKIN CONTACT!**

**— CONTAINS ORGANO-METALLIC TOXICANTS —**

#### MIXING PROCEDURE!

- Read and understand all directions regarding handling this material.
- Carefully pour catalyst into base, agitate until two components are well mixed.
- Allow at least 15 minutes induction time prior to application.
- This 100% solids coating — material will gel in package if left beyond the recommended pot life of 2-3 hours.
- **DO NOT ADD SOLVENT!**

**FOR ADDITIONAL DETAILS CONSULT  
MATERIAL SAFETY DATA SHEET**

Vessel may be launched when coating has cured for 48 hours

#### SURFACE PREPARATION

This coating is intended for application over either Imperial #120 Primer or Imperial #1230 as applied over blasted steel (SSPC-SP10 or SSPC-SP11).  
All surfaces must be clean and dry prior to application.  
On recoating previously coated hulls, a sand sweep and tie coat is recommended.

#### HANDLING PRECAUTIONS

- Toxicant may be absorbed through skin — therefore, avoid contact or inhalation of spray mist. Protective clothing is recommended.
- In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and seek prompt medical attention; wash skin with plenty of "Zest" or other heavy alkaline soap and water. Discard contaminated clothing; do not reuse.
- Consult Imperial Technical representative regarding the use of disposable clothing.
- Do not store near food and food products.

#### APPLICATION

- Airless spray is recommended. GRACO Bulldog (3001) with Golden Gun (.033 orifice).
- Air spray is slower alternate. Use "Eclipse" heavy mastic gun with 3/8" diameter nylon fluid hose.
- Brush or roller is acceptable.
- Check wet film thickness.
- Apply at 13-14 mils wet.
- **DO NOT ADD SOLVENT!**

**DO NOT CONTAMINATE WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.**  
**DO NOT REUSE THIS CONTAINER. DESTROY IT BY PERFORATING OR CRUSHING.**  
**BURY OR DISCARD IN A SAFE PLACE.**