ALGACIDE-L

WARNING-KEEP OUT REACH OF CHILDREN

HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. INJURIOUS TO EYES. CAUSES SKIN IRRITATION. RAPIDLY ABSORBED THROUGH SKIN.

DO NOT GET INTO EYES, ON SKIN OR CLOTHING.
WASH THOROUGHLY AFTER HANDLING. WASH CLOTHES BEFORE REUSE. KEEP
PACKAGE TIGHTLY CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION.

FIRST AID IN CASE OF CONTACT PLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN WASH WITH SOAP AND PLENTY OF WATER.

NOTE TO PHYSICIAN THIS PRODUCT IS A METABOLIC STIMULANT. CAUSES HYPERTHERMIA. TREAT SYMPTOMATICALLY.

THIS PRODUCT IS TOXIC TO FISH AND WILDLIFE. TREATED EFFLUENT SHOULD NOT BE DISCHARGED WHERE IT WILL DRAIN INTO LAKES, STREAMS, PONDS, OR PUBLIC WATER. USE ONLY AS DIRECTED.

ALGACIDU-L IS USED TO CONTROL ALGAE, BACTERIA, AND FUNGI IN RECIRCULATING COMMERCIAL AND INDUSTRIAL WATER COOLING TOWERS.

INITIAL DOSE: WHEN THE SYSTEM IS FOULED, APPLY A DOSE OF 53.7 TO 107.4 FLUID OUNCES PER 1,000 GALLONS OF WATER IN THE SYSTEM. REPEAT UNTIL CONTROL IS ACHIEVED.

SUBSEQUENT DOSE: WHEN MICROBIAL CONTROL IS EVIDENT, ADD 26.9 TO 53.7 FLUID OUNCES PER 1,000 GALLONS OF WATER IN THE SYSTEM EVERY 2-5 DAYS OR AS NEEDED TO MAINTAIN CONTROL. BADLY FOULED SYSTEMS MUST BE MANUALLY OR CHEMICALLY CLEANED BEFORE TREATMENT IS BEGUN. ALGACIDE-L MAY BE ADDED DIRECTLY TO THE SUMP OF WATER COOLING TOWERS.

E.P.A. REG. NO. 11576-2

• • • FOR CHEMICAL CONTROL OF ALGAE AND SLIME IN WATER COOLING TOWERS



314 Spears Ave. Phone 267-6781

	8-2-72
ACTIVE INGREDIENTS	DATE
SODIUM PENTACHLOROPHEN-	UNDER THE PEDERAL INSECTICIDE
ATE7.9%	EDICE FOR ECTN MILLIPORT STEELS
SODIUM SALT OF OTHER	
CHLOROPHENOLS1.15	TARE
TOTAL9.01	
INERT INGREDIENTS 91.04	NET
WEIGHT ONE GALLON-9.221b	CUSTOMER
DO NOT REUSE EMPTY DRUM.	ODDIUMLN
OR DESTROY BY PERFORATING	NIMRER
OR CRUSHING AND BURYING	MAMPEN
IN A SAFE PLACE.	

ACCEPTED