

ALGAECIDE - WS

DANGER-KEEP OUT OF REACH OF CHILDREN --SEE PRECAUTIONS BELOW

HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. INJURIOUS TO EYES. CAUSES IRRITATION. RAPIDLY ABSORBED THROUGH SKIN.

DO NOT GET INTO EYES, ON SKIN OR CLOTHING.

WASH THOROUGHLY AFTER HANDLING. KEEP PACKAGE TIGHTLY CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION.

FIRST AID
IN CASE OF CONTACT FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. FOR SKIN WASH WITH SOAP AND LOTS OF WATER.

FISH PRECAUTIONS

THIS PRODUCT IS TOXIC TO FISH. TREATED EFFLUENT SHOULD NOT BE DISCHARGED WHERE IT WILL DRAIN INTO LAKES, STREAMS, PONDS, OR PUBLIC WATER.

DIRECTIONS FOR USE

ALGAECIDE-WS IS USED TO CONTROL ALGAE, BACTERIA, AND FUNGI IN RECIRCULATION COMMERCIAL AND INDUSTRIAL WATER COOLING TOWERS. PRIOR TO ITS USE, SYSTEMS MUST BE CLEANED TO REMOVE ALGAE GROWTH, MICROBIOLOGICAL SLIME AND OTHER DEPOSITS. AN INITIAL SLUG ADDITION OF 2.9 TO 7.3 FLUID OUNCES OF ALGAECIDE-WS PER 1000 GALLONS OF WATER IS NEEDED TO PROVIDE A CONCENTRATION OF 24 TO 60 PARTS PER MILLION OF ALGAECIDE-WS BASED ON THE TOTAL WEIGHT OF WATER IN THE SYSTEM IS RECOMMENDED. SUBSEQUENT SLUG ADDITIONS OF 0.73 TO 7.3 FLUID OUNCES OF ALGAECIDE-WS PER 1000 GALLONS OF WATER ARE NEEDED TO PROVIDE 6 TO 60 PARTS PER MILLION OF ALGAECIDE-WS. THESE ADDITIONS SHOULD BE EMPLOYED EVERY TWO TO FIVE DAYS OR AS NEEDED. THE FREQUENCY OF ADDITION DEPENDS UPON THE RELATIVE AMOUNT OF BLEEDOFF AND THE SEVERITY OF THE MICROBIOLOGICAL PROBLEM. SLUG ADDITIONS SHOULD BE MADE IN THE SUMP OF WATER COOLING TOWERS.

E.P.A. REG. NO. 11576-5

FOR CHEMICAL CONTROL OF
INDUSTRIAL WATER PROBLEMS



314 Spears Ave. Phone 267-6781

ACTIVE INGREDIENTS----- 20.0%
Poly[oxyethylene(dimethyl-
iminio)ethylene(dimethyl-
iminio)ethylene dichloride]

----- 20.0%

INERT INGREDIENTS----- 80.0%

Weight One Gallon--8.69 lbs.

DO NOT REUSE DRUM. DESTROY
WHEN EMPTY.

ACCEPTED

9-12-72

Chemical

DATE

GROSS

TARE

NET

CUSTOMER

NUMBER