

INDUSTRIAL WATER MANAGEMENT

A 26 ALGAECIDE

A-26 Algaecide is used to inhibit the growth of algae, bacteria and fungi in recirculating commercial and industrial cooling water systems. Before treating with A-26 Algaecide systems must be cleaned to remove algal growth, microbiological slimes and other deposits. Then the system should be treated with an initial slug addition to a point of rapid circulation of 7 fluid ounces (60 ppm) to 14 fluid ounces (120 ppm) of A-26 Algaecide per 1,000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 2.5 fluid ounces (20 ppm) to 14 fluid ounces (120 ppm) of A-26 Algaecide per 1,000 gallons of water should be made every 1 to 5 days, or as needed. The required frequency of treatment depends on the relative amount of bleed-off and the severity of the microbiological problem. Slug additions should be made to a point of rapid circulation in water cooling tower sump or distribution trays.

Active Ingredients:-----	8.75%
Disodium Cyanodithioimidocarbonate-----	3.68%
Potassium N-methyldithiocarbamate-----	5.07%
Inert Ingredients-----	91.25%
Weight per gallon-----	8.81 Lbs.
Weight of Active Ingredients per Gallon-----	0.77 Lbs.

WARNING

KEEP OUT OF REACH OF CHILDREN

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes call physician. Remove and wash contaminated clothing before reuse.

If swallowed, give patient doses of powdered charcoal immediately or all be can swallow of raw egg white, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately. Do not reuse empty container. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

ACCEPTED

E.P.A. REG. NO. 11617-2

AUG 26 1975

E.P.A. EST. 11617-IL-1



REGISTERED
Pesticide Act
11617-2

Comments

IWM

P.O. BOX 130

corporation

ARLINGTON HEIGHTS, ILLINOIS 60006

ACCEPTED WITH COMMENTS