

SARINE B1 10
BROAD SPECTRUM FUNGICIDE
BACTERICIDE - ALGAECIDE
 EPA Reg. #11620-1

Ship to:

ACCEPTED
 11620-1
 FEB 21 1975
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND RODENTICIDE ACT
 FOR ECONOMIC POISON REGISTERED
 UNDER NO.

RECEIVED
 15 JAN 1975
 REGISTRATION DIVISION
 PESTICIDES, EPA



SARINE B1 10

Percent by weight

Active ingredient 10 percent
 Poly[oxyethylene(dimethyliminio)ethylene(dimethyliminio)-
 ethylene dichloride] 10 percent
 Inert ingredient 90 percent
 Weight per gallon 8.5 pounds
 Weight of active ingredient per gallon 0.84 pound

CAUTION
KEEP OUT OF THE
REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid skin contact. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not discharge effluent to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

APPLICATION

Sarine B1 10 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits.

An initial slug addition to 6.13 to 15.32 fluid ounces of Sarine B1 10 per 1,000 gallons of water, to provide a concentration of 48 to 120 parts per million of Sarine B1 10 based on the total weight of water in the system is recommended.

Repeat initial dosage until control is evident. Subsequent slug addition of 1.53 to 15.33 fluid ounces of Sarine B1 10 per 1,000 gallons of water (12 to 120 parts per million of Sarine B1 10) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleed-off and the severity of the microbiological problem. Slug addition should be made in the sump of water cooling towers.

— MANUFACTURED BY —

OLSEN CHEMICAL CO., INC.

62-64 E. 26th Street • Paterson, N. J. 07514 • (201) 525-2600