

#422 CARIBBEAN BLUE

Sea-worthy™

ANTI-FOULING BOTTOM PAINT

with TBTA*

WARNING

Use with adequate ventilation. Avoid breathing vapor or mist and prolonged contact with the skin. This product is a mild sensitizer to the skin. In case of contact, immediately flush eyes with plenty of water for 15 minutes and get prompt medical attention. Use protective breathing mask and protective clothing when sanding. Wash hands and other exposed skin areas with soap and water after use. Do not use, pour, spill, or store near heat or open flame. Keep container closed when not in use. Do not re-use empty container. Destroy it by perforating or crushing. May be fatal if swallowed. This product is sold for use only on boat bottoms for protection against marine fouling.

KEEP OUT OF CHILDREN'S REACH

FORMULA: No. 422 Caribbean Blue

COMPOSITION BY WEIGHT:

Bis (Tributyltin) Adipate	19.25%
Titanium Dioxide/Pigment	11.97%
Vinyl Resin/Rosin	10.84%
Tricresyl Phosphate	1.44%
Bentonite	0.49%
Methanol	0.15%
Aromatic Hydrocarbons	27.93%
Ketones	27.93%
Total	100.00%

Tin as Metallic - 6.353%

E.P.A. REG. NO. 11627-1



WARNING

See side panel for required precautions.

ONE QUART

KEEP OUT OF REACH OF CHILDREN

This new...
Hurry...

If old paint...
thoroughly...
before paint

- Sand pap...
- If a new...
to remove...
Fouling p...
Apply two

- Prepare...

- For sand...
allow to d...
apply two

- Aluminum...
with a hig...
Anti-Foul

- Outdrives...
cleaned i...
dry 30-2...
of 800-20

- For best...
followed...
copper pl

- If wooded...
Thinner.

- Caulk see...
costs of 1

NOTE:

- Clean bru

- Allow 3 t

- Final coat
- If Anti-Fo
- Coverage

Distributed By:
Western Products, Inc.
P.O. Box 745
Orange, Connecticut 06477