



USE: An air drying, copper base preservative for wood, fabric and rope. Will protect wood from drying, rot, fungi, and termites. Can be applied by dip, brush or spray, and will give long lasting protection. It has excellent penetrative properties, a high resistance to leaching, water insoluble, long lasting, and only a mild odor. The light green color is natural.

DIRECTIONS: Use as it comes from the package for extra protection. Remove all previous paint coatings and rot away all rotten wood. When used for termite protection, this product is intended to be used on wood to be used in structures, not for structures already in place.

MAY BE DILUTED: Dilute 1 part of this product with 1 part of mineral spirits, fuel oil or suitable petroleum solvent to produce 12.5% copper naphthenate solution.

FOR BRUSH OR SPRAY: Apply liberally using as many coats as necessary to secure penetration is required. Do not attempt to save material because the degree of protection afforded is dependent upon the amount that penetrates into the structure of the wood. Lumber intended to be in contact with soil should receive two or more flowing coats of the product.

FOR DIP: Length of time for soaking dependent upon thickness and type of wood. A minimum soaking time of 30 minutes suggested for thickness of 2" or less. Overnight soaking suggested in treating heavier timber. Frame posts, poles, foundation timbers, and heavy wooden members should be free of bark, dry and well seasoned and immersed in the product (in diluted product for a period of 12 to 48 hours) to be an effective wood preserver.

FOR CANVAS & ROPE: Apply liberally to saturate thoroughly. Let dry before using.

SURFACES TO BE PAINTED: Dilute this product as directed. Allow treated surface to dry 48 hours before painting. If white or light tints are used there might be a slight discoloration after first coat of paint is applied. This will disappear completely when second coat is applied. Wood is thoroughly dry.

COVERAGE: Varies by species and condition of wood. For general use estimate 200 to 450 sq. ft. per gallon.

This product is toxic to fish. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

EPA Est. No. 11655VA-1

**SAMPSON PAINT MANUFACTURING CO., INC.**

301 HULL STREET • RICHMOND, VIRGINIA 23224