

walling

Phone 605/336-6710
P.O. Box 408

chemical company

Sioux Falls, So. Dak. 57101

A-232X

**A COMPLETE MICROBICIDE FOR OPEN
RECIRCULATING COOLING SYSTEMS**

COMPOSITION

	Percent by Weight
Active ingredients	11.6 percent
Disodium cyanodithioimidocarbonate	4.90 percent
Potassium N-methyldithiocarbamate	6.76 percent
Inert ingredients	88.4 percent
Water	

ACCEPTED
AUG 1 1975
11658-8
Comment

APPLICATIONS

Walling A-232X is used to inhibit the growth of algae, bacteria, and fungi in recirculating commercial and industrial cooling water systems. Before treatment with Walling A-232X systems must be cleaned to remove algal growth, microbiological slime, and other deposits. Then the system should be treated with an initial slug addition of 6.9 to 13.9 fluid ounces of Walling A-232X per 1,000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 2.3 to 4.9 fluid ounces of Walling A-232X per 1,000 gallons of water should be made every 1 to 5 days or as needed. The required frequency of treatment depends on the relative amount of bleedoff and the severity of the microbiological problem. Slug additions of Walling A-232X should be made to the sump of water cooling towers.

WARNING— KEEP OUT OF REACH OF CHILDREN

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.
FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.
If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg white, milk, gelatin, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately.

Do not reuse empty drum. Return to manufacturer for instructions by post, return of drum, and leaving drum in place.

This product is toxic to fish. Treated effluent should be discharged where it will dilute into surface water, streams, or public water. Do not contaminate water with toxic materials, equipment, or disposal wastes. Apply this product only as specified on this label.

EPA Reg. No. 119-075

ACCEPTED WITH COMMENTS