

#4180 SUPER TROPICAL ANTI-FOULING

BPS ANTI-FOULING PAINT is recommended for use as a bottom paint from keel to light load line on commercial tankers and merchant ships sailing in tropic and temperate waters. It is formulated with a special hinder that will slowly leach and release the active ingredients which will inhibit plant growth and is poisonous to hard shell foulants such as barnacles, annelids, mollusks, etc.

DIRECTIONS FOR APPLICATION

Stir the paint thoroughly and apply 1 - 2 coats over BPS Primer #4176 Anti-Corrosive. Allow 4 - 6 hours dry between coats of BPS Anti-Fouling Paint. When the finish is dry to touch, 4 - 6 hours, the ship may be floated. Do not wait longer than 48 hours before floating. If thinner is needed, use BPS Thinner #3146 up to 1 pint per gallon. For clean equipment, brushes, rollers, spray equipment, use BPS Thinner #3146.

CAUTION: Contains Petroleum Distillate

If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. COMBUSTIBLE (Flash Point 105° F.) Keep away from heat and open flame. Avoid contact with skin and breathing of vapor or spray mist. Harmful if swallowed. Close container after each use. Do not use empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

KEEP OUT OF THE REACH OF CHILDREN.

Net Contents - 5 U.S. Gallons

GUARANTEED
TO GIVE
SATISFACTION
OR PURCHASE PRICE
WILL BE REFUNDED

PATTERSON-SARGENT

A **textron** DIVISION

NORTH BRUNSWICK, NEW JERSEY 08902 - TULSA, OKLAHOMA 74110



MANUFACTURERS OF QUALITY ALUMINUM BOATS

ANTI-FOULING BLUE

ACTIVE INGREDIENT	
bis(tributyltin) oxide	6.5%
INERT INGREDIENTS	93.5%

CAUTION

Keep Out of Reach of Children

See Back Panel for other Cautions

EPA Reg. No. 11699-1

CONTAINS
bioMET.
ANTI-FOULANT

Trad. mark
M. & T. Company

P. O. BOX 2306

FLORENCE ALABAMA 36660

ONE U.S. QUART

KING'S CRAFT ANTI-

SURFACE PREPARATION

Clean your hull **thoroughly** until free of all marine growth for scrapes; check adhesion of old paint film. Scrape "feather-edge" repaired areas. Spot prime all sanded bare water Primer (follow directions on label.) King's Craft Primer after application of primer.

APPLICATION

Paint only completely dry surfaces and only under favorable conditions until uniform in consistency. **DO NOT THIN.** Apply one roller - be careful not to leave "skips" or bare spots. Extended aging of this paint before launching does not. Clean brushes and rollers in a good grade of Vinyl Red. **DO NOT** add any thinners to this paint!

Note: Lower edge of Blue Water Line should be masked with Blue or Underwater Primer to get on water line or other result. Always remove masking tape immediately after use.

WARNING - FLAMMABLE

KEEP AWAY FROM HEAT

May be absorbed through skin. Avoid breathing spray. Avoid storage near food and feed products. Do not reuse swallowed. Do not get in eyes, on skin, or on clothing. hot water before reuse. In case of skin contact, remove skin with soap and water. For eyes, immediately flush with water.

mfg. by Edw. H. Marcus Paint