Professional Engineering Service

Manufacturing

**Chemists** 

ACCEPTED

Water Conditioning **Scale Removing** 

Steam and Cooling Systems

Postickies Beeniation Olvision, EPA

Laboratory **Controlled** 

FOR ECONOMIC POISON REGISTER.

Formula 215-25L

## **COMPOSITION**

ACTIVE INGREDIENTS:	1.72%
Alkyl ( $C_{14}$ –50%, $C_{12}$ –40%, $C_{16}$ –10%) Dimethyl Benzyl Ammonium Chloride 1.72	by weight
INERT INGREDIENTS	98.28%
Water	by weight

## **APPLICATION**

RUSTROL Formula 215-25L is used in industrial, commercial and institutional recirculating cooling water towers to control the growth of algae and fungi. Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. Badly fouled systems must be cleaned before treatment is begun. Apply at a point in the system where the product will be uniformly mixed.

For continuous feed methods, an initial dose of from 1.46 to

2.92 gallons of RUSTROL Formula 215-25L per 1000 gallons of water in the system. Apply half of this initial dose when half of the water in the system has been lost by bleed off. When control of microbial growth is evident, apply .486 to 1.46 gallons of RUSTROL 215-25L for each 1000 gallons of water lost from bleed off.

For intermittent feeding, an initial dose of from 1.46 to 2.92 gallons of RUSTROL Formula 215-25L per 1000 gallons of water in the system. Repeat until control is achieved. When microbial control is evident, add .486 to 1.46 gallons of RUSTROL Formula 215-25L per 1000 gallons of water in the system every 2 to 5 days, or as needed to maintain control.

## **CAUTION** KEEP OUT OF REACH OF CHILDREN.

Avoid contact with skin, eyes, and clothing.

First Aid: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label.

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies. (This applies to small containers.) For Drums: Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

EPA Reg. 11712-5

NET CONTENTS\_\_\_\_\_GAL.

MANUFACTURED BY

## WEST CHEMICAL & ENGINEERING CO., INC.

1187 HUFF ROAD, N. W.

TEL. 351-6449

TLANTA, GEORGIA 303"